



C.F.R. srl Modena - Italy	AC MOTOR IN WHEEL UNIT	CODE MRT05.A0100	Rev.: / Date:









Plug AMP Automotive Superseal 1.5
Series P2 282104-1
Thermic sensor STS1 U129

Plug AMP Automotive Superseal 1.5
Series P4 282106-1
Encoder ES 64 PPR


Traction motor data		
Type : AC Asynchronous		
Power (S2 - 60 min)	W	500
Motor voltage (~3)	V	16
Battery voltage	V	24
Speed	Rpm	2850
Frequency	Hz	100
Current	A	28
Torque	Nm	1.67
Enclosure	IP	20


Traction gear data		
Gear ratio	i	1:30.9
Max accel. and braking torque	Nm	180
Nominal wheel torque	Nm	39
Max load on vulkollan wheel	Kg	
Max load on poliurethan wheel	Kg	550
Max load on solid rubber wheel	Kg	400
Brake torque	Nm	4
Lubrication		Grease


Total Weight	Kg	21


Data : Date : 14/06/2018	Scala : Scale : 1 : 3.5	A3
Dis : Drawn : L.L.		


C.F.R. srl Modena - Italy	AC MOTOR IN WHEEL UNIT	CODE MRT05.A0101	Rev.: B Date: 26/04/21











Traction motor data		
Type : AC Asynchronous		
Power (S2 - 60 min)	W	500
Motor voltage (~3)	V	16
Battery voltage	V	24
Speed	Rpm	2850
Frequency	Hz	100
Current	A	28
Torque	Nm	1.67
Enclosure	IP	20

Traction gear data		
Gear ratio	i	1:30.9
Max accel. and braking torque	Nm	180
Nominal wheel torque	Nm	39
Max load on vulkollan wheel	Kg	
Max load on poliurethan wheel	Kg	550
Max load on solid rubber wheel	Kg	400
Brake torque	Nm	4
Lubrication		Grease

Steering gearmotor data		
Type : AC Asynchronous		
Power (S2 - 60 min)	W	150
Motor voltage (~3)	V	16
Battery voltage	V	24
Motor Speed	Rpm	2850
Frequency	Hz	100
Current	A	8
Motor torque	Nm	0.5
Gear ratio	i	1:46
Gear output torque	Nm	17.3
Enclosure	IP	20
Lubrication		Grease


Total Weight	Kg	42


Data : Date : 21/12/2016	Scala : Scale : 1 : 4	A3
Dis : Drawn : M.C.		


C.F.R. srl
Modena - Italy


D.C. MOTOR IN WHEEL UNIT

CODE **MRT05.DC001**









	Traction motor data		
1	Type : D.C. Permanent Magnet		
2	Power (S2 - 60 min)	W	400
3	Motor voltage	V	24
4			
5	Speed	rpm	2000
6			
7	Current	A	24
8	Torque	Nm	1.9
9			
10			
11	Enclosure	IP	20
12	Brake torque	Nm	4
	Traction gear data		
13	Max input motor power	W	500
14	Gear ratio	i	1:30.9
15	Max accel. and braking torque	Nm	180
16			
17	Nominal wheel torque	Nm	41
18			
19			
20			
21	Lubrication		Grease
22	Max load on vulkollan wheel	kg	600
23	Max load on polyurethan wheel	kg	550
24	Max load on solid rubber wheel	kg	400
	Steering gear motor data		
25	Type :		
26	Power (S2 - 60 min)	W	
27	Motor voltage	V	
28			
29	Motor Speed	rpm	
30			
31	Current	A	
32	Motor torque	Nm	
33	Enclosure	IP	
34			
35	Gear ratio	i	
36	Efficiency	η	

37	Total Weight	kg	23

	Available on request
A	Motors: Permanent Magnet, Series Wound, Sepex, AC Asynchronous
B	Voltages: 12V, 24V, 36V, 48V, 72V, 80V, 96V
C	Gear Ratio: 1:21, 1:26.9, 1:30.9
D	Encoders application ; Thermic Sensor
E	Forced ventilation
F	