PLUGS
OVERVIEW

Blanking Plugs
for Ports
Male Stud Connector with Captive seal

Blanking Plug
for Tube Ends
24° Cone End

Blanking Plug
for Cones
24° DKO Swivel

Blanking Plugs
for Ports
Male stud connector with O-ring


C-VSTI-WD

Blanking Plugs for Ports (M/R)

Male Metric Tread with Captive seal (ISO 9974 Type E)
Male BSPP Thread with Captive seal (ISO 1179 Type E)



C-VSTI-M-OR



PN [bar] C	PN [bar] CF	T	ØD1 [mm]	L1 [mm]	L2 [mm]	S1 [mm]	Ordering Code*	kg/ 100
400	400	M 10 x 1	14	12.0	8	5	**C-VSTI M 10 x 1 WD**	0.7
		M 12 x 1.5	17	17.0	12	6	**C-VSTI M 12 x 1.5 WD**	1.3
		M 14 x 1.5	19	17.0	12	6	**C-VSTI M 14 x 1.5 WD**	1.9
		M 16 x 1.5	22	17.0	12	8	**C-VSTI M 16 x 1.5 WD**	2.4
		M 18 x 1.5	24	17.0	12	8	**C-VSTI M 18 x 1.5 WD**	3.2
		M 20 x 1.5	26	19.0	14	10	**C-VSTI M 20 x 1.5 WD**	4
		M 22 x 1.5	27	19.0	14	10	**C-VSTI M 22 x 1.5 WD**	4.9
		M 26 x 1.5	32	21.0	16	12	**C-VSTI M 26 x 1.5 WD**	7.5
		M 27 x 2	32	21.0	16	12	**C-VSTI M 27 x 2 WD**	7.7
		M 33 x 2	40	22.5	16	17	**C-VSTI M 33 x 2 WD**	12.5
315	315	M 42 x 2	50	22.5	16	22	**C-VSTI M 42 x 2 WD**	20.7
		M 48 x 2	55	22.5	16	24	**C-VSTI M 48 x 2 WD**	27.2
400	400	G1/8 A	14	12.0	8	5	**C-VSTI R 1/8 WD**	0.7
		G1/4 A	19	17.0	12	6	**C-VSTI R 1/4 WD**	1.7
		G3/8 A	22	17.0	12	8	**C-VSTI R 3/8 WD**	2.6
		G1/2 A	27	19.0	14	10	**C-VSTI R 1/2 WD**	4.4
		G3/4 A	32	21.0	16	12	**C-VSTI R 3/4 WD**	7.5
		G1 A	40	22.5	16	17	**C-VSTI R 1 WD**	12.4
315	315	G1/4 A	50	22.5	16	22	**C-VSTI R 1 1/4 WD**	20.4
		G1/2 A	55	22.5	16	24	**C-VSTI R 1 1/2 WD**	26.7

*Replace the character "**C**" with "**CF**" when you require steel!
C = Stainless Steel, 1.4571 (Seal FKM) **CF** = Galvanized Steel Cr(VI)-free (Seal NBR)




C-VSTI-M-OR

Blanking Plugs for Ports

Metric Male Stud Connector O-Ring (ISO 6149)





PN [bar] C	PN [bar] CF	T	ØD1 [mm]	L1 [mm]	L2 [mm]	S1 [mm]	Ordering Code*	kg/ 100
630	630	M8X1	12	13.0	9.5	4	**C-VSTI M 8X1 OR**	0.5
		M10X1	14	13.5	9.5	5	**C-VSTI M 10X1 OR**	0.8
		M12X1.5	17	16.0	11.0	6	**C-VSTI M 12X1,5 OR**	1.3
		M14X1.5	19	16.0	11.0	6	**C-VSTI M 14X1,5 OR**	1.9
		M16X1.5	22	17.5	12.5	8	**C-VSTI M 16X1,5 OR**	2.5
		M18X1,5	24	19.0	14.0	8	**C-VSTI M 18X1,5 OR**	3.5
		M22X1,5	27	20.0	15.0	10	**C-VSTI M 22X1,5 OR**	5.2
400	400	M26X1,5	31	21.0	16.0	12	**C-VSTI M 26X1,5 OR**	7.5
		M27X2	32	23.5	18.5	12	**C-VSTI M 27X2 OR**	8.6
		M33X2	41	25.0	18.5	17	**C-VSTI M 33X2 OR**	14.2
		M42X2	50	25.5	19.0	22	**C-VSTI M 42X2 OR**	23.1
		M48X2	55	28.0	21.5	24	**C-VSTI M 48X2 OR**	32.6

*Replace the character "**C**" with "**CF**" when you require steel!
C = Stainless Steel, 1.4571 (Seal FKM) **CF** = Galvanized Steel Cr(VI)-free (Seal NBR)

CONEXA
www.CONEXA.de Phone: +49 5541 9877 -0 Fax: +49 5541 9877 -77



C-ROV


Blanking Plug for Tube Ends


24° Tube Connection
(DIN EN ISO 8434-1)



C-VKA







Series	PN [bar] C	PN [bar] CF	ØD1 [mm]	L1 [mm]	L2 [mm]	L3 [mm]	S1 [mm]	S2 [mm]	Ordering Code*	kg/ 100
L	315	315	6	14	7.0	22	12	14	**C-ROV 06 L X**	0.9
			8	15	8.0	23	14	17	**C-ROV 08 L X**	1.3
			10	16	9.0	24	17	19	**C-ROV 10 L X**	1.8
			12	17	10.0	25	19	22	**C-ROV 12 L X**	2.5
			15	18	11.0	26	24	27	**C-ROV 15 L X**	4.2
			18	19	11.5	28	27	32	**C-ROV 18 L X**	5.9
	160	160	22	21	13.5	30	32	36	**C-ROV 22 L X**	8.5
			28	22	14.5	31	41	41	**C-ROV 28 L X**	13.8
			35	25	14.5	36	46	50	**C-ROV 35 L X**	20.7
			42	27	16.0	39	55	60	**C-ROV 42 L X**	31.3
S	630	630	6	18	11.0	26	14	17	**C-ROV 06 S X**	1.8
			8	20	13.0	28	17	19	**C-ROV 08 S X**	2.8
			10	20	12.5	29	19	22	**C-ROV 10 S X**	3.4
			12	22	14.5	31	22	24	**C-ROV 12 S X**	5.0
			14	24	16.0	34	24	27	**C-ROV 14 S X**	6.4
	400	400	16	24	15.5	34	27	30	**C-ROV 16 S X**	7.7
			20	28	17.5	39	32	36	**C-ROV 20 S X**	12.8
			25	32	20.0	44	41	46	**C-ROV 25 S X**	23.2
			30	34	20.5	47	46	50	**C-ROV 30 S X**	30.6
	250	315	38	39	23.0	54	55	60	**C-ROV 38 S X**	51.9

*Replace the character "**C**" with "**CF**" when you require steel!
C = Stainless Steel, 1.4571 (Seal FKM) **CF** = Galvanized Steel Cr(VI)-free (Seal NBR)

CONEXA www.CONEXA.de Phone: +49 5541 9877 -0 Fax: +49 5541 9877 -77




C-VKA

Blanking Plug for Cones

24° Cone
(DIN EN ISO 8434-1)



Components Overview



Series	PN [bar] C	PN [bar] CF	ØD1 [mm]	L1 [mm]	Ordering Code*	kg/ 100
L	315	500	6	18.5	**C-VKA 06 L**	0.6
			8	18.5	**C-VKA 08 L**	0.9
			10	20.0	**C-VKA 10 L**	1.5
	315	400	12	20.5	**C-VKA 12 L**	2.2
			15	20.5	**C-VKA 15 L**	3.2
			18	22.5	**C-VKA 18 L**	5.0
	160	250	22	25.0	**C-VKA 22 L**	8.2
			28	25.5	**C-VKA 28 L**	13.2
			35	30.0	**C-VKA 35 L**	24.2
			42	30.0	**C-VKA 42 L**	34.4
S	630	800	6	18.5	**C-VKA 06 S**	0.6
			8	18.5	**C-VKA 08 S**	0.9
			10	20.0	**C-VKA 10 S**	1.5
	630	630	12	20.5	**C-VKA 12 S**	2.2
			14	22.5	**C-VKA 14 S**	3.0
	400	630	16	23.5	**C-VKA 16 S**	4.1
	400	400	20	28.5	**C-VKA 20 S**	7.9
			25	29.0	**C-VKA 25 S**	12.1
			30	30.5	**C-VKA 30 S**	18.2
	315	400	38	33.0	**C-VKA 38 S**	31.1

*Replace the character "**C**" with "**CF**" when you require steel!
C = Stainless Steel, 1.4571 (Seal FKM) **CF** = Galvanized Steel Cr(VI)-free (Seal NBR)

CONEXA www.CONEXA.de Phone: +49 5541 9877 -0 Fax: +49 5541 9877 -77