

MCVFB-08

单向阀
Check Valve



机能符号 Symbol



技术参数 Specifications


· 工作压力 Operating Pressure	350BAR
· 流量 Flow	38L/min
· 内泄漏 Internal Leakage	5drop/min.max.at operating pressure
· 温度 Temperature	-30°C to +120°C(-22°F to+250°F)
· 插孔 Cavity	08-2 see page K-9
· 流体 Fluids	Mineral-based fluids with viscosities of 7.4 to 420 cSt.

产品特性 Features

· 硬化处理, 零件耐久性强
Hardened,precision ground parts for durability
· 工业通用插孔
Industry common cavity
· 紧凑的结构
Compact size
· 低泄漏设计
Low leakage design

压力-流量性能曲线
Performance Curve Pressure Drop vs.Flow


150ssu/32 cSt OIL@100°F/38°C



工作 Operation

当在①口的压力超过开启压力, ①到②开启;在反方向, ②到①关闭;
Pressure at ① overcomes the spring-bias poppet and allows free flow ① to ②.Flow in the opposite direction,from ② to ①, is blocked by the poppet.

安装尺寸 INSTALLATION DIMENSIONS



D

订购型号 Order Type

MCVFB-08 – * – * – * *

I II III IV

Ⅰ. 开启压力 Cracking Pressure
0.34=5psi(0.34bar)
0.7=10psi(0.7bar)
1.7=25psi(1.7bar)
3.4=50psi(3.4bar)

Ⅱ. 油封 Seal-Kits
N=丁腈橡胶 Buna N
V=氟橡胶 Viton

Ⅲ. 阀块材质 BODY MATERIAL
A=6061-T6铝
耐压强度207Bar
6061-T6 aluminum
alloy rated at 207Bar
S=钢材 耐压强度350Bar
steel rated at 350Bar

Ⅳ. 阀块油口 BODY PORTING
4T=SAE 4T
8T=SAE 8T
3G=G3/8
3N=NPT3/8
其他螺纹油口是可选择的
Other porting is available