

C-GEO

Male Stud Connector

Metric Male Stud Connector O-Ring (ISO 6149) / 24° Tube Connection (DIN EN ISO 8434-1)







Series	PN [bar] C	PN [bar] CF	ØD1 [mm]	T	ØD3 [mm]	ØD4 [mm]	L1 [mm]	L2 [mm]	L3 [mm]	L4 [mm]	S1 [mm]	S2 [mm]	Ordering Code *	kg/ 100
LL	100	100	4	M08x1	3.0	11	20.0	9.5	6.5	19.0	11	10	**C-GEO 04 LLM OMD**	0.9
			4	M10x1	3.0	13	20.0	9.5	6.5	19.0	13	10	**C-GEO 04 LLM 10x1 OMD**	1.1
			6	M10x1	4.5	13	20.0	8.0	6.5	19.5	13	12	**C-GEO 06 LLM OMD**	1.0
L	315	500	6	M10x1	4.5	14	24.0	8.5	8.5	23.0	14	14	**C-GEO 06 LM OMD**	1.4
			8	M12x1.5	6.0	17	28.0	10.0	11.0	25.0	17	17	**C-GEO 08 LM OMD**	2.3
			10	M14x1.5	7.5	19	29.0	11.0	11.0	26.0	19	19	**C-GEO 10 LM OMD**	2.7
	315	400	12	M16x1.5	9.0	22	31.0	12.5	11.5	27.0	22	22	**C-GEO 12 LM OMD**	4.0
			15	M18x1.5	11.0	24	33.0	13.5	12.5	29.0	24	27	**C-GEO 15 LM OMD**	5.5
			18	M22x1.5	14.0	27	35.0	14.5	13.0	31.0	27	32	**C-GEO 18 LM OMD**	7.9
	160	250	22	M27x2	18.0	32	40.0	16.5	16.0	33.0	32	36	**C-GEO 22 LM 27x2 OMD**	10.3
			28	M33x2	23.0	41	41.0	17.5	16.0	34.0	41	41	**C-GEO 28 LM OMD**	17.0
			35	M42x2	30.0	50	44.0	17.5	16.0	39.0	50	50	**C-GEO 35 LM OMD**	27.8
			42	M48x2	36.0	55	47.5	19.0	17.5	42.0	55	60	**C-GEO 42 LM OMD**	34.0
S	630	800	6	M12x1.5	4.0	17	31.0	13.0	11.0	28.0	17	17	**C-GEO 06 SM OMD**	2.8
			8	M14x1.5	6.0	19	33.0	15.0	11.0	30.0	19	19	**C-GEO 08 SM OMD**	4.0
			10	M16x1.5	7.0	22	35.0	15.0	12.5	31.0	22	22	**C-GEO 10 SM OMD**	5.4
	630	630	12	M18x1.5	9.0	24	38.5	17.0	14.0	33.0	24	24	**C-GEO 12 SM OMD**	7.3
	400	630	16	M22x1.5	12.0	27	42.0	18.5	15.0	37.0	27	30	**C-GEO 16 SM OMD**	10.1
	400	400	20	M27x2	15.0	32	49.5	20.5	18.5	42.0	32	36	**C-GEO 20 SM OMD**	16.7
			25	M33x2	20.0	41	53.5	23.0	18.5	47.0	41	46	**C-GEO 25 SM OMD**	27.3
			30	M42x2	26.0	50	56.0	23.5	19.0	50.0	50	50	**C-GEO 30 SM OMD**	41.0
	250	400	38	M48x2	32.0	55	63.5	26.0	21.5	57.0	55	60	**C-GEO 38 SM OMD**	58.1

*Replace the character "**C**" with "**CF**" when you require steel!
C = Stainless Steel, 1.4571 (Seal FKM) **CF** = Galvanized Steel Cr(VI)-free (Seal NBR)





C-GE-R-WD

Male stud connector (LL, L)

Male BSPP Thread with Captive seal (ISO 1179) / 24° Tube Connection (DIN EN ISO 8434-1)







Series	PN [bar] C	PN [bar] CF	ØD1 [mm]	T	ØD3 [mm]	ØD4 [mm]	L1 [mm]	L2 [mm]	L3 [mm]	L4 [mm]	S1 [mm]	S2 [mm]	Ordering Code *	kg/ 100
LL	100	100	4	G1/8A	3	14	21.5	9.5	8	19.5	14	10	**C-GE 04 LLR WD OMD**	1.0
	100	100	6	G1/8A	4	14	21.5	8.0	8	19.5	14	12	**C-GE 06 LLR WD OMD**	1.1
L	315	315	6	G1/8A	4	14	23.5	8.5	8	23.5	14	14	**C-GE 06 LR WD OMD**	1.4
	315	500	6	G1/4A	4	19	29.0	10.0	12	25.0	19	14	**C-GE 06 LR 1/4 WD OMD**	3.0
	315	400	6	G3/8A	4	22	30.5	11.5	12	26.5	22	14	**C-GE 06 LR 3/8 WD OMD**	4.5
	315	400	6	G1/2A	4	27	33.0	12.0	14	27.0	27	14	**C-GE 06 LR 1/2 WD OMD**	6.0
	315	500	8	G1/4A	6	19	29.0	10.0	12	25.0	19	17	**C-GE 08 LR WD OMD**	2.7
	315	500	8	G1/8A	4	14	24.5	9.5	8	24.5	14	17	**C-GE 08 LR 1/8 WD OMD**	1.6
	315	400	8	G3/8A	6	22	30.5	11.5	12	26.5	22	17	**C-GE 08 LR 3/8 WD OMD**	4.7
	315	400	8	G1/2A	6	27	33.0	12.0	14	27.0	27	17	**C-GE 08 LR 1/2 WD OMD**	7.5
	315	500	10	G1/4A	6	19	30.0	11.0	12	26.0	19	19	**C-GE 10 LR WD OMD**	3.0
	315	315	10	G1/8A	4	14	25.5	10.5	8	25.5	17	19	**C-GE 10 LR 1/8 WD OMD**	2.2
	315	400	10	G3/8A	8	22	31.5	12.5	12	27.5	22	19	**C-GE 10 LR 3/8 WD OMD**	4.1
	315	400	10	G1/2A	8	27	34.0	13.0	14	28.0	27	19	**C-GE 10 LR 1/2 WD OMD**	5.2
	315	400	12	G3/8A	9	22	31.5	12.5	12	27.5	22	22	**C-GE 12 LR WD OMD**	4.1
	315	400	12	G1/8A	4	14	26.5	11.5	8	26.5	19	22	**C-GE 12 LR 1/8 WD OMD**	2.6
	315	400	12	G1/4A	6	19	31.0	12.0	12	27.0	19	22	**C-GE 12 LR 1/4 WD OMD**	3.0
	315	400	12	G1/2A	10	27	34.0	13.0	14	28.0	27	22	**C-GE 12 LR 1/2 WD OMD**	6.5
	160	250	12	G3/4A	10	32	37.0	14.0	16	29.0	32	22	**C-GE 12 LR 3/4 WD OMD**	11.9
	315	400	15	G1/2A	11	27	35.0	14.0	14	29.0	27	27	**C-GE 15 LR WD OMD**	7.1
	315	400	15	G3/8A	9	22	32.5	13.5	12	28.5	24	27	**C-GE 15 LR 3/8 WD OMD**	4.9
	160	250	15	G3/4A	12	32	38.0	15.0	16	30.0	32	27	**C-GE 15 LR 3/4 WD OMD**	12.0
	315	400	18	G1/2A	14	27	36.0	14.5	14	31.0	27	32	**C-GE 18 LR WD OMD**	7.0
	315	400	18	G3/8A	9	22	33.5	14.0	12	30.5	27	32	**C-GE 18 LR 3/8 WD OMD**	6.6
	160	250	18	G3/4A	15	32	38.0	14.5	16	31.0	32	32	**C-GE 18 LR 3/4 WD OMD**	13.4
	160	250	22	G3/4A	18	32	40.0	16.5	16	33.0	32	36	**C-GE 22 LR WD OMD**	10.4
	160	250	22	G1/2A	14	27	38.0	16.5	14	33.0	32	36	**C-GE 22 LR 1/2 WD OMD**	9.1
	160	250	22	G1A	19	40	43.0	17.5	18	34.0	41	36	**C-GE 22 LR 1 WD OMD**	19.0
	160	250	28	G1A	23	40	43.0	17.5	18	34.0	41	41	**C-GE 28 LR WD OMD**	16.5
	160	250	28	G3/4A	18	32	41.0	17.5	16	34.0	41	41	**C-GE 28 LR 3/4 WD OMD**	16.0
	160	250	28	G1 1/4A	24	50	46.0	18.5	20	35.0	50	41	**C-GE 28 LR 11/4 WD OMD**	26.2
	160	250	35	G1 1/4A	30	50	48.0	17.5	20	39.0	50	50	**C-GE 35 LR WD OMD**	27.5
	160	250	35	G1A	23	40	46.0	17.5	18	39.0	46	50	**C-GE 35 LR 1 WD OMD**	22.6
	160	250	35	G1 1/2A	30	55	52.0	19.5	22	41.0	55	50	**C-GE 35 LR 11/2 WD OMD**	42.0
	160	250	42	G1 1/2A	36	55	52.0	19.0	22	42.0	55	60	**C-GE 42 LR WD OMD**	34.5
	160	250	42	G1A	23	40	48.0	19.0	18	42.0	55	60	**C-GE 42 LR 1 WD OMD**	32.2
	160	250	42	G1 1/4A	30	50	50.0	19.0	20	42.0	55	60	**C-GE 42 LR 11/4 WD OMD**	34.0

*Replace the character "**C**" with "**CF**" when you require steel!
C = Stainless Steel, 1.4571 (Seal FKM) **CF** = Galvanized Steel Cr(VI)-free (Seal NBR)

CONEXA www.CONEXA.de Phone: +49 5541 9877 -0 Fax: +49 5541 9877 -77




C-GE-R-WD


Male Stud Connector (S)

Male BSPP Thread with Captive seal (ISO 1179) /
24° Tube Connection (DIN EN ISO 8434-1)



C-GE-M-WD





Series	PN [bar] C	PN [bar] CF	ØD1 [mm]	T	ØD3 [mm]	ØD4 [mm]	L1 [mm]	L2 [mm]	L3 [mm]	L4 [mm]	S1 [mm]	S2 [mm]	Ordering Code *	kg/ 100
S	630	800	6	G1/4A	4	19	32.0	13.0	12	28.0	19	17	**C-GE 06 SR WD OMD**	3.5
	315	315	6	G1/8A	4	14	27.5	12.5	8	27.5	14	17	**C-GE 06 SR 1/8 WD OMD**	2.2
	630	630	6	G3/8A	4	22	34.5	15.5	12	30.5	22	17	**C-GE 06 SR 3/8 WD OMD**	5.2
	400	630	6	G1/2A	4	27	39.0	18.0	14	33.0	27	17	**C-GE 06 SR 1/2 WD OMD**	8.2
	630	800	8	G1/4A	5	19	34.0	15.0	12	30.0	19	19	**C-GE 08 SR WD OMD**	4.0
	630	800	8	G3/8A	5	22	34.5	15.5	12	30.5	22	19	**C-GE 08 SR 3/8 WD OMD**	6.1
	400	630	8	G1/2A	5	27	39.0	18.0	14	33.0	27	19	**C-GE 08 SR 1/2 WD OMD**	8.8
	630	800	10	G3/8A	7	22	34.5	15.0	12	31.5	22	22	**C-GE 10 SR WD OMD**	5.5
	630	800	10	G1/4A	5	19	34.0	14.5	12	31.0	19	22	**C-GE 10 SR 1/4 WD OMD**	4.7
	630	630	10	G1/2A	7	27	39.0	17.5	14	34.0	27	22	**C-GE 10 SR 1/2 WD OMD**	13.8
	630	630	12	G3/8A	8	22	36.5	17.0	12	33.5	22	24	**C-GE 12 SR WD OMD**	6.2
	630	630	12	G1/4A	5	19	36.0	16.5	12	33.0	22	24	**C-GE 12 SR 1/4 WD OMD**	5.7
	630	630	12	G1/2A	8	27	39.0	17.5	14	34.0	27	24	**C-GE 12 SR 1/2 WD OMD**	9.5
	630	630	14	G1/2A	10	27	41.0	19.0	14	37.0	27	27	**C-GE 14 SR WD OMD**	9.8
	630	630	14	G3/8A	8	22	38.5	18.5	12	36.5	24	27	**C-GE 14 SR 3/8 WD OMD**	7.4
	400	400	14	G3/4A	10	32	45.0	21.0	16	39.0	32	27	**C-GE 14 SR 3/4 WD OMD**	13.9
	400	630	16	G1/2A	12	27	41.0	18.5	14	37.0	27	30	**C-GE 16 SR WD OMD**	9.3
	400	630	16	G3/8A	8	22	38.5	18.0	12	36.5	27	30	**C-GE 16 SR 3/8 WD OMD**	8.5
	400	400	16	G3/4A	12	32	45.0	20.5	16	39.0	32	30	**C-GE 16 SR 3/4 WD OMD**	15.4
	400	400	20	G3/4A	16	32	47.0	20.5	16	42.0	32	36	**C-GE 20 SR WD OMD**	15.0
	400	400	20	G1/2A	12	27	45.0	20.5	14	42.0	32	36	**C-GE 20 SR 1/2 WD OMD**	14.1
	400	400	20	G1A	16	40	51.0	22.5	18	44.0	41	36	**C-GE 20 SR 1 WD OMD**	26.0
	400	400	20	G1 1/4A	16	50	53.0	22.5	20	44.0	50	36	**C-GE 20 SR 1 1/4 WD OMD**	40.2
	400	400	25	G1A	20	40	53.0	23.0	18	47.0	41	46	**C-GE 25 SR WD OMD**	27.0
	400	400	25	G1/2A	12	27	49.0	23.0	14	47.0	41	46	**C-GE 25 SR 1/2 WD OMD**	23.0
	400	400	25	G3/4A	16	32	51.0	23.0	16	47.0	41	46	**C-GE 25 SR 3/4 WD OMD**	24.5
	400	400	25	G1 1/4A	20	50	55.0	23.0	20	47.0	50	46	**C-GE 25 SR 1 1/4 WD OMD**	41.0
	315	315	25	G1 1/2A	20	55	60.0	26.0	22	50.0	55	46	**C-GE 25 SR 1 1/2 WD OMD**	55.0
	400	400	30	G1 1/4A	25	50	57.0	23.5	20	50.0	50	50	**C-GE 30 SR WD OMD**	42.0
	400	400	30	G1A	20	40	55.0	23.5	18	50.0	46	50	**C-GE 30 SR 1 WD OMD**	34.0
	315	315	30	G1 1/2A	25	55	62.0	26.5	22	53.0	55	50	**C-GE 30 SR 1 1/2 WD OMD**	56.0
	250	400	38	G1 1/2A	32	55	64.0	26.0	22	57.0	55	60	**C-GE 38 SR WD OMD**	56.5
	250	400	38	G1 1/4A	25	50	62.0	26.0	20	57.0	55	60	**C-GE 38 SR 1 1/4 WD OMD**	57.0

*Replace the character "**C**" with "**CF**" when you require steel!
C = Stainless Steel, 1.4571 (Seal FKM) **CF** = Galvanized Steel Cr(VI)-free (Seal NBR)

CONEXA www.CONEXA.de Phone: +49 5541 9877 -0 Fax: +49 5541 9877 -77



C-GE-M-WD


Male Stud Connector


Male BSPP Thread with Captive seal (ISO 1179) /
24° Tube Connection (DIN EN ISO 8434-1)





C-GE-R (L)





Series	PN [bar] C	PN [bar] CF	ØD1 [mm]	T	ØD3 [mm]	ØD4 [mm]	L1 [mm]	L2 [mm]	L3 [mm]	L4 [mm]	S1 [mm]	S2 [mm]	Ordering Code *	kg/ 100
LL	100	100	4	G1/8A	3	14	21.5	9.5	8	19.5	14	10	**C-GE 04 LLR WD OMD**	1.0
	100	100	6	G1/8A	4	14	21.5	8.0	8	19.5	14	12	**C-GE 06 LLR WD OMD**	1.1
L	315	315	6	G1/8A	4	14	23.5	8.5	8	23.5	14	14	**C-GE 06 LR WD OMD**	1.4
	315	500	6	G1/4A	4	19	29.0	10.0	12	25.0	19	14	**C-GE 06 LR 1/4 WD OMD**	3.0
	315	400	6	G3/8A	4	22	30.5	11.5	12	26.5	22	14	**C-GE 06 LR 3/8 WD OMD**	4.5
	315	400	6	G1/2A	4	27	33.0	12.0	14	27.0	27	14	**C-GE 06 LR 1/2 WD OMD**	6.0
	315	500	8	G1/4A	6	19	29.0	10.0	12	25.0	19	17	**C-GE 08 LR WD OMD**	2.7
	315	500	8	G1/8A	4	14	24.5	9.5	8	24.5	14	17	**C-GE 08 LR 1/8 WD OMD**	1.6
	315	400	8	G3/8A	6	22	30.5	11.5	12	26.5	22	17	**C-GE 08 LR 3/8 WD OMD**	4.7
	315	400	8	G1/2A	6	27	33.0	12.0	14	27.0	27	17	**C-GE 08 LR 1/2 WD OMD**	7.5
	315	500	10	G1/4A	6	19	30.0	11.0	12	26.0	19	19	**C-GE 10 LR WD OMD**	3.0
	315	315	10	G1/8A	4	14	25.5	10.5	8	25.5	17	19	**C-GE 10 LR 1/8 WD OMD**	2.2
	315	400	10	G3/8A	8	22	31.5	12.5	12	27.5	22	19	**C-GE 10 LR 3/8 WD OMD**	4.1
	315	400	10	G1/2A	8	27	34.0	13.0	14	28.0	27	19	**C-GE 10 LR 1/2 WD OMD**	5.2
	315	400	12	G3/8A	9	22	31.5	12.5	12	27.5	22	22	**C-GE 12 LR WD OMD**	4.1
	315	400	12	G1/8A	4	14	26.5	11.5	8	26.5	19	22	**C-GE 12 LR 1/8 WD OMD**	2.6
	315	400	12	G1/4A	6	19	31.0	12.0	12	27.0	19	22	**C-GE 12 LR 1/4 WD OMD**	3.0
	315	400	12	G1/2A	10	27	34.0	13.0	14	28.0	27	22	**C-GE 12 LR 1/2 WD OMD**	6.5
	160	250	12	G3/4A	10	32	37.0	14.0	16	29.0	32	22	**C-GE 12 LR 3/4 WD OMD**	11.9
	315	400	15	G1/2A	11	27	35.0	14.0	14	29.0	27	27	**C-GE 15 LR WD OMD**	7.1
	315	400	15	G3/8A	9	22	32.5	13.5	12	28.5	24	27	**C-GE 15 LR 3/8 WD OMD**	4.9
	160	250	15	G3/4A	12	32	38.0	15.0	16	30.0	32	27	**C-GE 15 LR 3/4 WD OMD**	12.0
	315	400	18	G1/2A	14	27	36.0	14.5	14	31.0	27	32	**C-GE 18 LR WD OMD**	7.0
	315	400	18	G3/8A	9	22	33.5	14.0	12	30.5	27	32	**C-GE 18 LR 3/8 WD OMD**	6.6
	160	250	18	G3/4A	15	32	38.0	14.5	16	31.0	32	32	**C-GE 18 LR 3/4 WD OMD**	13.4
	160	250	22	G3/4A	18	32	40.0	16.5	16	33.0	32	36	**C-GE 22 LR WD OMD**	10.4
	160	250	22	G1/2A	14	27	38.0	16.5	14	33.0	32	36	**C-GE 22 LR 1/2 WD OMD**	9.1
	160	250	22	G1A	19	40	43.0	17.5	18	34.0	41	36	**C-GE 22 LR 1 WD OMD**	19.0
	160	250	28	G1A	23	40	43.0	17.5	18	34.0	41	41	**C-GE 28 LR WD OMD**	16.5
	160	250	28	G3/4A	18	32	41.0	17.5	16	34.0	41	41	**C-GE 28 LR 3/4 WD OMD**	16.0
	160	250	28	G1 1/4A	24	50	46.0	18.5	20	35.0	50	41	**C-GE 28 LR 11/4 WD OMD**	26.2
	160	250	35	G1 1/4A	30	50	48.0	17.5	20	39.0	50	50	**C-GE 35 LR WD OMD**	27.5
	160	250	35	G1A	23	40	46.0	17.5	18	39.0	46	50	**C-GE 35 LR 1 WD OMD**	22.6
	160	250	35	G1 1/2A	30	55	52.0	19.5	22	41.0	55	50	**C-GE 35 LR 11/2 WD OMD**	42.0
	160	250	42	G1 1/2A	36	55	52.0	19.0	22	42.0	55	60	**C-GE 42 LR WD OMD**	34.5
	160	250	42	G1A	23	40	48.0	19.0	18	42.0	55	60	**C-GE 42 LR 1 WD OMD**	32.2
	160	250	42	G1 1/4A	30	50	50.0	19.0	20	42.0	55	60	**C-GE 42 LR 11/4 WD OMD**	34.0

*Replace the character "**C**" with "**CF**" when you require steel!
C = Stainless Steel, 1.4571 (Seal FKM) **CF** = Galvanized Steel Cr(VI)-free (Seal NBR)

CONEXA www.CONEXA.de Phone: +49 5541 9877 -0 Fax: +49 5541 9877 -77





C-GE-R

Male stud connector (L)

Male BSPP Thread with Metal Sealing Edge (ISO 1179) /
24° Tube Connection (DIN EN ISO 8434-1)







Series	PN [bar] C	PN [bar] CF	ØD1 [mm]	T	ØD3 [mm]	ØD4 [mm]	L1 [mm]	L2 [mm]	L3 [mm]	L4 [mm]	S1 [mm]	S2 [mm]	Ordering Code *	kg/ 100
L	315	315	6	G1/8A	4	14	23.5	8.5	8	23.5	14	14	**C-GE 06 LR X**	1.4
			6	G1/4A	4	18	29.0	10.0	12	25.0	19	14	**C-GE 06 LR 1/4 X**	2.9
			6	G3/8A	4	22	30.5	11.5	12	26.5	22	14	**C-GE 06 LR 3/8 X**	4.5
			6	G1/2A	4	26	33.0	12.0	14	27.0	27	14	**C-GE 06 LR 1/2 X**	6.0
			8	G1/4A	6	18	29.0	10.0	12	25.0	19	17	**C-GE 08 LR X**	2.7
			8	G1/8A	4	14	24.5	9.5	8	24.5	14	17	**C-GE 08 LR 1/8 X**	1.7
			8	G3/8A	6	22	30.5	11.5	12	26.5	22	17	**C-GE 08 LR 3/8 X**	4.4
			8	G1/2A	6	26	33.0	12.0	14	27.0	27	17	**C-GE 08 LR 1/2 X**	7.3
			10	G1/4A	6	18	30.0	11.0	12	26.0	19	19	**C-GE 10 LR X**	2.9
			10	G1/8A	4	14	25.5	10.5	8	25.5	17	19	**C-GE 10 LR 1/8 X**	2.1
			10	G3/8A	8	22	31.5	12.5	12	27.5	22	19	**C-GE 10 LR 3/8 X**	4.4
			10	G1/2A	8	26	34.0	13.0	14	28.0	27	19	**C-GE 10 LR 1/2 X**	7.1
			12	G3/8A	9	22	31.5	12.5	12	27.5	22	22	**C-GE 12 LR X**	4.3
			12	G1/8A	4	14	26.5	11.5	8	26.5	19	22	**C-GE 12 LR 1/8 X**	2.7
			12	G1/4A	6	18	31.0	12.0	12	27.0	19	22	**C-GE 12 LR 1/4 X**	3.3
			12	G1/2A	10	26	34.0	13.0	14	28.0	27	22	**C-GE 12 LR 1/2 X**	6.7
			12	G3/4A	10	32	37.0	14.0	16	29.0	32	22	**C-GE 12 LR 3/4 X**	12.0
	250	250	15	G1/2A	11	26	35.0	14.0	14	29.0	27	27	**C-GE 15 LR X**	6.6
			15	G3/8A	9	22	32.5	13.5	12	28.5	22	27	**C-GE 15 LR 3/8 X**	5.6
			15	G3/4A	12	32	38.0	15.0	16	30.0	32	27	**C-GE 15 LR 3/4 X**	11.6
			18	G1/2A	14	26	36.0	14.5	14	31.0	27	32	**C-GE 18 LR X**	7.1
			18	G3/8A	9	22	33.5	14.0	12	30.5	27	32	**C-GE 18 LR 3/8 X**	6.9
			18	G3/4A	15	32	38.0	14.5	16	31.0	32	32	**C-GE 18 LR 3/4 X**	11.1
	160	160	22	G3/4A	18	32	40.0	16.5	16	33.0	32	36	**C-GE 22 LR X**	10.2
			22	G1/2A	14	26	38.0	16.5	14	33.0	32	36	**C-GE 22 LR 1/2 X**	8.7
			22	G1A	19	39	43.0	17.5	18	34.0	41	36	**C-GE 22 LR 1 X**	18.5
			28	G1A	23	39	43.0	17.5	18	34.0	41	41	**C-GE 28 LR X**	16.7
			28	G1/2A	14	26	39.0	17.5	14	34.0	41	41	**C-GE 28 LR 1/2 X**	14.0
			28	G3/4A	18	32	41.0	17.5	16	34.0	41	41	**C-GE 28 LR 3/4 X**	14.3
			28	G1 1/4A	24	49	46.0	18.5	20	35.0	50	41	**C-GE 28 LR 1 1/4 X**	31.2
			35	G1 1/4A	30	49	48.0	17.5	20	28.0	50	50	**C-GE 35 LR X**	27.6
			35	G1/2A	14	27	42.0	17.5	14	39.0	46	50	**C-GE 35 LR 1/2 X**	19.4
			35	G3/4A	18	32	44.0	17.5	16	39.0	46	50	**C-GE 35 LR 3/4 X**	20.2
			35	G1A	23	39	46.0	17.5	18	39.0	46	50	**C-GE 35 LR 1 X**	23.4
			35	G1 1/2A	30	55	52.0	19.5	22	41.0	55	50	**C-GE 35 LR 1 1/2 X**	35.5
			42	G1 1/2A	36	55	52.0	19.0	22	42.0	55	60	**C-GE42 LR X**	35.2
			42	G1A	23	39	48.0	19.0	18	42.0	55	60	**C-GE42 LR 1 X**	32.6
			42	G1 1/4A	30	49	50.0	19.0	20	42.0	55	60	**C-GE42 LR 1 1/4 X**	33.5

*Replace the character "**C**" with "**CF**" when you require steel!
C = Stainless Steel, 1.4571 **CF** = Galvanized Steel Cr(VI)-free

CONEXA
www.CONEXA.de Phone: +49 5541 9877 -0 Fax: +49 5541 9877 -77



C-GE-R


Male Stud Connector (S)


Male BSPP Thread with Metal Sealing Edge (ISO 1179) /
24° Tube Connection (DIN EN ISO 8434-1)





C-GE-M





Series	PN [bar] C	PN [bar] CF	ØD1 [mm]	T	ØD3 [mm]	ØD4 [mm]	L1 [mm]	L2 [mm]	L3 [mm]	L4 [mm]	S1 [mm]	S2 [mm]	Ordering Code *	kg/ 100
S	400	400	6	G1/4A	4	18	32.0	13.0	12	28.0	19	17	**C-GE 06 SR X**	3.6
	315	315	6	G1/8A	3	14	27.5	12.5	8	27.5	14	17	**C-GE 06 SR 1/8 X**	2.2
			6	G3/8A	4	22	34.5	15.5	12	30.5	22	17	**C-GE 06 SR 3/8 X**	5.8
			6	G1/2A	4	26	39.0	18.0	14	33.0	27	17	**C-GE 06 SR 1/2 X**	8.3
			8	G1/4A	5	18	34.0	15.0	12	30.0	19	19	**C-GE 08 SR X**	4.1
			8	G3/8A	5	22	34.5	15.5	12	30.5	22	19	**C-GE 08 SR 3/8 X**	5.8
			8	G1/2A	5	26	39.0	18.0	14	33.0	27	19	**C-GE 08 SR 1 X/2 X**	10.2
			10	G3/8A	7	22	34.5	15.0	12	31.5	22	22	**C-GE 10 SR X**	5.7
			10	G1/4A	5	18	34.0	14.5	12	31.0	19	22	**C-GE 10 SR 1/4 X**	4.0
			10	G1/2A	7	26	39.0	17.5	14	34.0	27	22	**C-GE 10 SR 1/2 X**	9.7
			12	G3/8A	8	22	36.5	17.0	12	33.5	22	24	**C-GE 12 SR X**	6.3
			12	G1/4A	5	18	36.0	16.5	12	33.0	22	24	**C-GE 12 SR 1/4 X**	5.7
			12	G1/2A	8	26	39.0	17.5	14	34.0	27	24	**C-GE 12 SR 1/2 X**	9.7
			14	G1/2A	10	26	41.0	19.0	14	37.0	27	27	**C-GE 14 SR X**	9.6
			14	G3/8A	8	22	38.5	18.5	12	36.5	24	27	**C-GE 14 SR 3/8 X**	7.4
			16	G1/2A	12	26	41.0	18.5	14	37.0	27	30	**C-GE 16 SR X**	9.1
			16	G3/8A	8	22	38.5	18.0	12	36.5	27	30	**C-GE 16 SR 3/8 X**	8.6
			16	G3/4A	12	32	45.0	20.5	16	39.0	32	30	**C-GE 16 SR 3/4 X**	15.5
			20	G3/4A	16	32	47.0	20.5	16	42.0	32	36	**C-GE 20 SR X**	15.2
			20	G1/2A	12	26	45.0	20.5	14	42.0	32	36	**C-GE 20 SR 1/2 X**	13.6
	250	250	20	G1A	16	39	51.0	22.5	18	44.0	41	36	**C-GE 20 SR 1 X**	27.2
	160	160	20	G1 1/4A	16	49	53.0	22.5	20	44.0	50	36	**C-GE 20 SR 1 1/4 X**	38.5
	250	250	25	G1A	20	39	53.0	23.0	18	47.0	41	46	**C-GE 25 SR X**	26.9
			25	G3/4A	16	32	51.0	23.0	16	47.0	41	46	**C-GE 25 SR 3/4 X**	24.3
	160	160	25	G1 1/4A	20	49	55.0	23.0	20	47.0	50	46	**C-GE 25 SR 1 1/4 X**	42.0
			30	G1 1/4A	25	49	57.0	23.5	20	50.0	50	50	**C-GE 30 SR X**	42.3
			30	G1A	20	39	55.0	23.5	18	50.0	46	50	**C-GE 30 SR 1 X**	33.7
			38	G1 1/2A	32	55	64.0	26.0	22	57.0	55	60	**C-GE 38 SR X**	56.8
			38	G1 1/4A	25	49	62.0	26.0	20	57.0	55	60	**C-GE 38 SR 1 1/4 X**	56.7

*Replace the character "**C**" with "**CF**" when you require steel!
C = Stainless Steel, 1.4571 **CF** = Galvanized Steel Cr(VI)-free

CONEXA
www.CONEXA.de Phone: +49 5541 9877 -0 Fax: +49 5541 9877 -77




C-GE-M


Male Stud Connector

Metric Male Stud Connector with Sealing Edge (ISO 9974) / 24° Tube Connection (DIN EN ISO 8434-1)



C-GE-R-KEG





Series	PN [bar] C	PN [bar] CF	ØD1 [mm]	T	ØD3 [mm]	ØD4 [mm]	L1 [mm]	L2 [mm]	L3 [mm]	L4 [mm]	S1 [mm]	S2 [mm]	Ordering Code *	kg/ 100
L	315	315	6	M10x1	4	14	23.5	8.5	8	23.5	14	14	**C-GE 06 LM X**	1.4
			8	M12x1.5	6	17	29.0	10.0	12	25.0	17	17	**C-GE 08 LM X**	2.3
			10	M14x1.5	7	19	30.0	11.0	12	26.0	19	19	**C-GE 10 LM X**	2.9
			10	M10x1	4	14	25.5	10.5	8	25.5	17	19	**C-GE 10 LM 10x1 X**	2.0
			10	M12x1.5	6	17	30.0	11.0	12	26.0	17	19	**C-GE 10 LM 12x1.5 X**	2.5
			10	M16x1.5	8	21	31.5	12.5	12	27.5	22	19	**C-GE 10 LM 16x1.5 X**	4.0
			10	M18x1.5	8	23	31.5	12.5	12	27.5	24	19	**C-GE 10 LM 18x1.5 X**	5.0
			10	M22x1.5	8	27	35.0	14.0	14	29.0	27	19	**C-GE 10 LM 22x1.5 X**	7.6
			12	M14x1.5	7	19	30.0	11.0	12	26.0	19	22	**C-GE 12 LM 14x1.5 X**	3.0
			12	M16x1.5	9	21	31.5	12.5	12	27.5	22	22	**C-GE 12 LM X**	4.0
			12	M18x1.5	10	23	31.5	12.5	12	27.5	24	22	**C-GE 12 LM 18x1.5 X**	4.7
			12	M22x1.5	10	27	35.0	14.0	14	29.0	27	22	**C-GE 12 LM 22x1.5 X**	7.3
	250	250	15	M16x1.5	9	21	32.0	13.0	12	28.0	24	27	**C-GE 15 LM 16x1.5 X**	5.0
			15	M18x1.5	11	23	32.5	13.5	12	28.5	24	27	**C-GE 15 LM X**	5.2
			15	M22x1.5	12	27	36.0	15.0	14	30.0	27	27	**C-GE 15 LM 22x1.5 X**	7.4
			18	M18x1,5	11	23	33.5	14.0	12	30.5	27	32	**C-GE 18 LM 18x1.5 X**	6.4
			18	M22x1.5	14	24	36.0	14.5	14	31.0	27	32	**C-GE 18 LM X**	7.6
	160	160	22	M22x1.5	14	27	38.0	16.5	14	33.0	32	36	**C-GE 22 LM 22x1.5 X**	9.2
			22	M26x1.5	18	31	40.0	16.5	16	33.0	32	36	**C-GE 22 LM X**	10.1
			28	M33x2	23	39	43.0	17.5	18	34.0	41	41	**C-GE 28 LM X**	16.7
			35	M42x2	30	49	48.0	17.5	20	39.0	50	50	**C-GE 35 LM X**	28.2
			42	M48x2	36	55	52.0	19.0	22	42.0	55	60	**C-GE 42 LM X**	35.8
S	400	400	6	M12x1.5	4	17	32.0	13.0	12	28.0	17	17	**C-GE 06 SM X**	3.0
			6	M14x1.5	4	19	34.0	15.0	12	30.0	19	17	**C-GE 06 SM 14x1.5 X**	4.2
			8	M14x1.5	5	19	34.0	15.0	12	30.0	19	19	**C-GE 08 SM X**	4.3
			10	M16x1.5	7	21	34.5	15.0	12	31.5	22	22	**C-GE 10 SM X**	5.5
			12	M18x1.5	8	23	36.5	17.0	12	33.5	24	24	**C-GE 12 SM X**	7.2
			12	M14x1.5	5	19	36.0	16.5	12	33.0	22	24	**C-GE 12 SM 14x1.5 X**	6.0
			12	M22x1.5	8	27	39.0	17.5	14	34.0	27	24	**C-GE 12 SM 22x1.5 X**	10.3
			14	M20x1.5	10	25	41.0	19.0	14	37.0	27	27	**C-GE 14 SM X**	9.4
			16	M18x1.5	8	23	38.5	18.0	12	36.5	27	30	**C-GE 16 SM 18x1.5 X**	9.5
			16	M22x1.5	12	27	41.0	18.5	14	37.0	27	30	**C-GE 16 SM X**	9.8
			20	M27x2	16	32	47.0	20.5	16	42.0	32	36	**C-GE 20 SM X**	15.3
	250	250	25	M33x2	20	39	53.0	23.0	18	47.0	41	46	**C-GE 25 SM X**	26.9
	160	160	30	M42x2	25	49	57.0	23.5	20	50.0	50	50	**C-GE 30 SM X**	42.8
			38	M48x2	32	55	64.0	26.0	22	57.0	55	60	**C-GE 38 SM X**	57.5

*Replace the character "**C**" with "**CF**" when you require steel!
C = Stainless Steel, 1.4571 **CF** = Galvanized Steel Cr(VI)-free

CONEXA
www.CONEXA.de Phone: +49 5541 9877 -0 Fax: +49 5541 9877 -77



C-GE-R-KEG


Male Stud Connector


Male BSPP Stud Connector - Tapered (DIN 3852-2 Type C) / 24° Tube Connection (DIN EN ISO 8434-1)



C-GE-M-KEG
(LL)







Series	PN [bar] C	PN [bar] CF	ØD1 [mm]	T	ØD3 [mm]	L1 [mm]	L2 [mm]	L3 [mm]	L4 [mm]	S1 [mm]	S2 [mm]	Ordering Code *	kg/ 100
LL	100	100	4	R1/8KEG	3.0	20	16.0	8	26	11	10	**C-GE 04 LLR KEG X**	0.8
			6	R1/8KEG	4.5	20	14.5	8	26	11	12	**C-GE 06 LLR KEG X**	1.0
			8	R1/8KEG	6.0	22	16.5	8	28	12	14	**C-GE 08 LLR KEG X**	1.0
			8	R1/4KEG	6.0	26	20.5	12	32	14	14	**C-GE 08 LLR 1/4 KEG X**	2.0
			10	R1/4KEG	8.0	26	20.5	12	32	14	17	**C-GE 10 LLR KEG X**	2.4
			12	R1/4KEG	8.0	26	20.0	12	32	17	19	**C-GE 12 LLR KEG X**	5.3
			12	R3/8KEG	10.0	26	20.0	12	32	17	19	**C-GE 12 LLR 3/8 KEG X**	3.3
L	315	315	6	R1/8KEG	4.0	22	15.0	8	30	12	14	**C-GE 06 LR 1/8 KEG X**	1.1
			6	R1/4KEG	4.0	27	20.0	12	35	17	14	**C-GE 06 LR 1/4 KEG X**	2.0
			8	R1/8KEG	4.0	23	16.0	8	31	17	17	**C-GE 08 LR 1/8 KEG X**	1.5
			8	R1/4KEG	6.0	27	20.0	12	35	17	17	**C-GE 08 LR 1/4 KEG X**	2.0
			10	R1/4KEG	7.0	28	21.0	12	36	17	19	**C-GE 10 LR 1/4 KEG X**	2.4
			12	R1/4KEG	7.0	29	22.0	12	37	19	22	**C-GE 12 LR 1/4 KEG X**	3.0
			12	R3/8KEG	9.0	29	22.0	12	37	19	22	**C-GE 12 LR 3/8 KEG X**	3.4
			12	R1/2KEG	10.0	31	24.0	14	39	24	22	**C-GE 12 LR 1/2 KEG X**	4.9
			15	R3/8KEG	9.0	30	23.0	12	38	24	27	**C-GE 15 LR 3/8 KEG X**	4.8
			15	R1/2KEG	11.0	32	25.0	14	40	24	27	**C-GE 15 LR 1/2 KEG X**	5.4
			18	R1/2KEG	14.0	33	25.5	14	42	27	32	**C-GE 18 LR 1/2 KEG X**	6.4
	160	160	22	R3/4KEG	17.0	37	29.5	16	46	32	36	**C-GE 22 LR 3/4 KEG X**	9.8
			28	R1KEG	23.0	40	32.5	18	49	41	41	**C-GE 28 LR 1 KEG X**	15.4
			35	R1 1/4KEG	30.0	45	34.5	20	56	46	50	**C-GE 35 LR 1 1/4 KEG X**	23.5
			42	R1 1/2KEG	36.0	49	38.0	22	61	55	60	**C-GE 42 LR 1 1/2 KEG X**	33.4

*Replace the character "**C**" with "**CF**" when you require steel!
C = Stainless Steel, 1.4571 **CF** = Galvanized Steel Cr(VI)-free

CONEXA
www.CONEXA.de Phone: +49 5541 9877 -0 Fax: +49 5541 9877 -77