

REDUCING/RELIEVING VALVE
(Pilot Operated Reducing/Relieving)

Ordering Code:	**PP-2A-X-Y-Z**	



UNIT:mm


Illustrations / detail are for reference only. Data subject to change.



TECHNICAL DATA

Max.Operating pressure:	350	bar
Rated flow:	80	l/min
Cavity-Tooling:	2A-3	
Installation torque:	60 - 70	Nm
Weight:	0.264 (**Z**=L)	kg


· Control Pilot Flow (0.16 - 0.25 L/min.)



X	**OPERATION**	
30	Standard type (With filter)	
∗33	Very good pressure control (With filter) Improved dynamic response	
35	Impact resistant type (Without filter)	

Y	**SPRINGS** ADJUSTMENT RANGES (Recommended Differential Pressure) (X=30)(X=35)	
A	7 - 210 bar (14 bar Standard Setting) test at 350 bar inlet pressure	
B	3.5 - 105 bar (14 bar Standard Setting) Maximum Differential=210 bar	
D	1.7 - 55 bar (14 bar Standard Setting) Maximum Differential=140 bar	
E	1.7 - 28 bar (14 bar Standard Setting) Maximum Differential=140 bar	
H	2 - 210 bar (14 bar Standard Setting) test at 210 bar inlet pressure	
J	1.7 - 105 bar (14 bar Standard Setting) Maximum Differential=140 bar	
K	5 - 105 bar (14 bar Standard Setting) Maximum Differential=230 bar	
N	4 - 55 bar (14 bar Standard Setting) Maximum Differential=210 bar	
Q	4 - 28 bar (14 bar Standard Setting) Maximum Differential=210 bar	
S	1.7 - 14 bar (7 bar Standard Setting) Maximum Differential=140 bar	
W	10.5 - 315 bar (14 bar Standard Setting) test at 350 bar inlet pressure	

∗ When X = 33, the lowest pressure will be a bit higher than standard.
Any technical questions, please feel free to consult with our sales dept.

Z	**OPTIONS**	
L	Leakproof hex. socket screw. 	
LP	Leakproof hex. socket screw. With stainless steel external metal components 	
K	Handknob with Lock Knob. (Order Code: 6ZAK001) 