PU SH98
BINATO / TWIN



Caratteristiche principali

- **Pressione da 9 a 19 bar**
- **Temperatura di utilizzo da -20°C a +60°C**
- **Ideali per l'automazioni industriale**
- **Disponibile anche spiralato**

Main features

- ***Pressure from 9 to 19 bar***
- ***Working temperature from -20°C to +60°C***
- ***Ideal for industrial automation***
- ***Also available in spirals***

Caratteristiche tecniche

- **Caratteristiche tecnico-costruttive:**

Tubazioni binate in poliuretano poliestere. Durezza Shore A 98. Ottima flessibilità, memoria di forma e resistenza all'abrasione. Colorazione nera suggerita per applicazioni all'esterno.

- **Applicazioni:**

Automazione industriale, circuiti ad aria compressa nel settore alimentare, passaggio olii idraulici e lubrificanti. Idoneo per passaggio in catene portacavi.

- **Temperature di utilizzo:**

-20°C +60°C

- **Rapporto di sicurezza:**

1:3

- **Specifiche:**

FDA 21 CFR 177.2600

Technical Features

- ***Technical-constructive features:***

Polyurethane twin-line tubing ester based. Shore A 98 hardness. Excellent flexibility, elastic memory and abrasion resistance. Black colour recommended for outdoor applications.

- ***Applications:***

Industrial automation, compressed air circuits in food sector, hydraulics and lubricating oil conductions. Suitable for installing inside energy chains.

- ***Working temperatures:***

-20°C +60°C

- ***Safety ratio:***

1:3

- ***Specifications:***

FDA 21 CFR 177.2600

Scheda tecnica - *Data Sheet*

CODE	Twin-line tubing type	mm (ID)	mm (OD)	bar (1:3 WP)	mm (R MIN)	Colors	g/m
MPU422	2 TUBING 4x1 BLUE/BLACK	2	4	19	11	N-B	23
MPU4252	2 TUBING 4x0,75 BLUE/BLACK	2.5	4	13	15	N-B	19
MPU642	2 TUBING 6x1 BLUE/BLACK	4	6	13	18	N-B	39
MPU862	2 TUBING 8x1 BLUE/BLACK	6	8	9	35	N-B	54
MPU8552	2 TUBING 8x1,25 BLUE/BLACK	5.5	8	12	30	N-B	65
MPU852	2 TUBING 8x1,5 BLUE/BLACK	5	8	17	25	N-B	75

N: Black B: Blue

Nota: nel codice compare un *, bisogna sostituirlo con la sigla del colore del tubo.

*Note: there is an * in the code. This should be replaced with the color code of the tubing.*