NON-ADJUSTABLE MALE STUDS OVERVIEW

Adjustable
Male Studs
Overview

Male Stud Elbow
Male Stud Connector - Tapered / 24° Tube Connection

Male Stud Elbow
Male stud connector with sealing edge / 24° Tube Connection

Male Stud Elbow
Male Stud Connector - NPT / 24° Tube Connection

Male Metric Stud Branch T
Male Stud Connector - Tapered / 24° Tube Connection

Male Metric Stud Branch T
Male stud connector with sealing edge / 24° Tube Connection

Male Metric Stud Branch T
Male Stud Connector - NPT / 24° Tube Connection

Male Stud-Run T
Male Stud Connector - Tapered 24° Tube Connection

Male Stud-Run T
Male stud connector with sealing edge / 24° Tube Connection

Male Stud-Run T
Male Stud Connector - NPT / 24° Tube Connection


C-WE-R-KEG


Male Stud Elbow

Male BSPP Stud Connector - Tapered (DIN 3858-2 Type C) / 24° Tube Connection (DIN EN ISO 8434-1)



C-WE-M-KEG





Series	PN [bar] C	PN [bar] CF	ØD1 [mm]	T	ØD3 [mm]	ØD4 [mm]	L1 [mm]	L2 [mm]	L3 [mm]	L5 [mm]	S1 [mm]	S2 [mm]	Ordering Code *	kg/ 100
LL	100	100	4	R1/8 KEG	3.0	4.0	15	11.0	17	21	9	10	**C-WE 04 LLR KEG X**	1.2
			6	R1/8 KEG	4.5	4.5	15	9.5	17	21	9	12	**C-WE 06 LLR KEG X**	1.3
			8	R1/8 KEG	6.0	6.0	17	11.5	20	23	12	14	**C-WE 08 LLR KEG X**	1.4
			10	R1/4 KEG	8.0	7.0	21	15.5	26	27	12	17	**C-WE 10 LLR KEG X**	2.3
			12	R1/4 KEG	10.0	7.0	21	15.0	27	27	14	19	**C-WE 12 LLR KEG X**	2.9
L	315	315	6	R1/8 KEG	4.0	4.0	19	12.0	20	27	12	14	**C-WE 06 LR KEG X**	2.0
			6	R1/4 KEG	4.0	6.0	21	14.0	26	29	12	14	**C-WE 06 LR 1/4 KEG X**	2.8
			8	R1/4 KEG	6.0	6.0	21	14.0	26	29	12	17	**C-WE 08 LR KEG X**	2.9
			8	R1/8 KEG	6.0	4.0	21	14.0	26	29	12	17	**C-WE 08 LR 1/8 KEG X**	2.6
			8	R3/8 KEG	6.0	9.0	24	17.0	28	32	17	17	**C-WE 08 LR 3/8 KEG X**	5.0
			10	R1/4 KEG	8.0	7.0	22	15.0	27	30	14	19	**C-WE 10 LR KEG X**	3.5
			10	R3/8 KEG	8.0	9.0	24	17.0	28	32	17	19	**C-WE 10 LR 3/8 KEG X**	5.0
			12	R3/8 KEG	10.0	9.0	24	17.0	28	32	17	22	**C-WE 12 LR KEG X**	5.0
			12	R1/4 KEG	10.0	7.0	24	17.0	27	32	17	22	**C-WE 12 LR 1/4 KEG X**	4.8
			12	R1/2 KEG	10.0	11.0	28	21.0	34	36	19	22	**C-WE 12 LR 1/2 KEG X**	8.8
			15	R1/2 KEG	12.0	11.0	28	21.0	34	36	19	27	**C-WE 15 LR KEG X**	9.3
			18	R1/2 KEG	15.0	14.0	31	23.5	36	40	24	32	**C-WE 18 LR KEG X**	11.2
S	400	400	6	R1/4 KEG	4.0	4.0	23	16.0	26	31	12	17	**C-WE 06 SR KEG X**	3.8
			6	R3/8 KEG	4.0	7.0	25	18.0	28	33	17	17	**C-WE 06 SR 3/8 KEG X**	6.2
			8	R1/4 KEG	5.0	5.0	24	17.0	27	32	14	19	**C-WE 08 SR KEG X**	4.7
			8	R3/8 KEG	5.0	7.0	25	18.0	28	33	17	19	**C-WE 08 SR 3/8 KEG X**	6.3
			10	R3/8 KEG	7.0	7.0	25	17.5	28	34	17	22	**C-WE 10 SR KEG X**	6.3
			10	R1/4 KEG	7.0	5.0	25	17.5	28	34	17	22	**C-WE 10 SR 1/4 KEG X**	5.9
			10	R1/2 KEG	7.0	10.0	30	22.5	32	39	19	22	**C-WE 10 SR 1/2 KEG X**	10.6
			12	R3/8 KEG	8.0	8.0	29	21.5	28	38	17	24	**C-WE 12 SR KEG X**	7.5
			12	R1/2 KEG	8.0	11.0	30	22.5	32	39	19	24	**C-WE 12 SR 1/2 KEG X**	10.2
			14	R1/2 KEG	10.0	10.0	30	22.0	32	40	19	27	**C-WE 14 SR KEG X**	10.0
			16	R1/2 KEG	12.0	12.0	33	24.5	32	43	24	30	**C-WE 16 SR KEG X**	13.0

*Replace the character "**C**" with "**CF**" when you require steel!
C = Stainless Steel, 1.4571 **CF** = Galvanized Steel Cr(VI)-free

CONEXA www.CONEXA.de Phone: +49 5541 9877 -0 Fax: +49 5541 9877 -77




C-WE-M-KEG


Male Stud Elbow

Metric Male Stud Connector - Tapered (DIN 3852-1 Type C) / 24° Tube Connection (DIN EN ISO 8434-1)



C-WE-R





Series	PN [bar] C	PN [bar] CF	ØD1 [mm]	T	ØD3 [mm]	ØD4 [mm]	L1 [mm]	L2 [mm]	L3 [mm]	L5 [mm]	S1 [mm]	S2 [mm]	Ordering Code *	kg/ 100
LL	100	100	4	M8x1 KEG	3.0	3.5	15	11.0	17	21	9	10	**C-WE 04 LLM KEG X**	1.0
			6	M10x1 KEG	4.5	4.5	15	9.5	17	21	9	12	**C-WE 06 LLM KEG X**	1.1
			8	M10x1 KEG	6.0	6.0	17	11.5	20	23	12	14	**C-WE 08 LLM KEG X**	1.5
L	315	315	6	M10x1 KEG	4.0	4.0	19	12.0	20	27	12	14	**C-WE 06 LM KEG X**	2.0
			8	M12x1.5 KEG	6.0	6.0	21	14.0	26	29	12	17	**C-WE 08 LM KEG X**	2.6
			10	M14x1.5 KEG	8.0	7.0	22	15.0	27	30	14	19	**C-WE 10 LM KEG X**	3.8
			12	M16x1.5 KEG	10.0	9.0	24	17.0	28	32	17	22	**C-WE 12 LM KEG X**	4.8
			15	M18x1,5 KEG	12.0	11.0	28	21.0	32	36	19	27	**C-WE 15 LM KEG X**	8.0
			18	M22x1,5 KEG	15.0	14.0	31	23.5	36	40	24	32	**C-WE 18 LM KEG X**	11.8
S	400	400	6	M12x1.5 KEG	4.0	4.0	23	16.0	26	31	12	17	**C-WE 06 SM KEG X**	3.5
			8	M14x1.5 KEG	5.0	5.0	24	17.0	27	32	14	19	**C-WE 08 SM KEG X**	4.8
			10	M16x1.5 KEG	7.0	7.0	25	17.5	28	34	17	22	**C-WE 10 SM KEG X**	6.0
			12	M18x1,5 KEG	8.0	8.0	29	21.5	28	38	17	24	**C-WE 12 SM KEG X**	7.8
			14	M20x1,5 KEG	10.0	10.0	30	22.0	32	40	19	27	**C-WE 14 SM KEG X**	10.5
			16	M22x1,5 KEG	12.0	12.0	33	24.5	32	43	24	30	**C-WE 16 SM KEG X**	13.5

*Replace the character "**C**" with "**CF**" when you require steel!
C = Stainless Steel, 1.4571 **CF** = Galvanized Steel Cr(VI)-free

CONEXA www.CONEXA.de Phone: +49 5541 9877 -0 Fax: +49 5541 9877 -77




C-WE-R


Male Stud Elbow

Male BSPP Thread with Metal Sealing Edge (ISO 1179) /
24° Tube Connection (DIN EN ISO 8434-1)



C-WE-M





Series	PN [bar] C	PN [bar] CF	ØD1 [mm]	T	ØD3 [mm]	ØD4 [mm]	ØD5 [mm]	L1 [mm]	L2 [mm]	L3 [mm]	L4 [mm]	L5 [mm]	S1 [mm]	S2 [mm]	Ordering Code *	kg/ 100
L	160	160	22	G3/4A	19	18	32	35	27.5	26	16	44	27	36	**C-WE 22 LR X**	16.8
			28	G1A	24	23	39	38	30.5	30	18	47	36	41	**C-WE 28 LR X**	30.5
			35	G1 1/4A	30	30	49	45	34.5	34	20	56	41	50	**C-WE 35 LR X**	46.5
			42	G1 1/2A	36	36	55	51	40.0	39	22	63	50	60	**C-WE 42 LR X**	70.6
S	400	400	20	G3/4A	16	16	32	37	26.5	26	16	48	27	36	**C-WE 20 SR X**	21.0
	250	250	25	G1A	20	20	39	42	30.0	30	18	54	36	46	**C-WE 25 SR X**	38.8
	160	160	30	G1 1/4A	25	25	49	49	35.5	34	20	62	41	50	**C-WE 30 SR X**	63.0
			38	G1 1/2A	32	32	55	57	41.0	39	22	72	50	60	**C-WE 38 SR X**	88.0

*Replace the character "**C**" with "**CF**" when you require steel!
C = Stainless Steel, 1.4571 **CF** = Galvanized Steel Cr(VI)-free

CONEXA
www.CONEXA.de Phone: +49 5541 9877 -0 Fax: +49 5541 9877 -77



C-WE-M


Male Stud Elbow


Metric Male Stud Connector with Sealing Edge (ISO 9974) /
24° Tube Connection (DIN EN ISO 8434-1)





C-WE-NPT





Series	PN [bar] C	PN [bar] CF	ØD1 [mm]	T	ØD3 [mm]	ØD4 [mm]	ØD5 [mm]	L1 [mm]	L2 [mm]	L3 [mm]	L4 [mm]	L5 [mm]	S1 [mm]	S2 [mm]	Ordering Code *	kg/ 100
L	160	160	22	M26x1.5	19	18	31	35	27.5	26	16	44	27	36	**C-WE 22 LM X**	17.0
			28	M33x2	24	23	39	38	30.5	30	18	47	36	41	**C-WE 28 LM X**	30.5
			35	M42x2	30	30	49	45	34.5	34	20	56	41	50	**C-WE 35 LM X**	46.0
			42	M48x2	36	36	55	51	40.0	39	22	63	50	60	**C-WE 42 LM X**	67.5
S	400	400	20	M27x2	16	16	32	37	26.5	26	16	48	27	36	**C-WE 20 SM X**	21.0
	250	250	25	M33x2	20	20	39	42	30.0	30	18	54	36	46	**C-WE 25 SM X**	39.5
	160	160	30	M42x2	25	25	49	49	35.5	34	20	62	41	50	**C-WE 30 SM X**	62.5
			38	M48x2	32	32	55	57	41.0	39	22	72	50	60	**C-WE 38 SM X**	90.0

*Replace the character "**C**" with "**CF**" when you require steel!
C = Stainless Steel, 1.4571 **CF** = Galvanized Steel Cr(VI)-free

CONEXA
www.CONEXA.de Phone: +49 5541 9877 -0 Fax: +49 5541 9877 -77




C-WE-NPT


Male Stud Elbow

NPT-Male Stud Connector (SAE J476) /
24° Tube Connection (DIN EN ISO 8434-1)



C-TE-R-KEG





Series	PN [bar] C	PN [bar] CF	ØD1 [mm]	T	ØD3 [mm]	ØD4 [mm]	L1 [mm]	L2 [mm]	L3 [mm]	L5 [mm]	S1 [mm]	S2 [mm]	Ordering Code *	kg/ 100
LL	100	100	4	1/8-27 NPT	3.0	4.0	15	11.0	17	21	9	10	**C-WE 04 LL 1/8 NPT X**	1.2
			6	1/8-27 NPT	4.5	4.5	15	9.5	17	21	9	12	**C-WE 06 LL 1/8 NPT X**	1.1
			8	1/8-27 NPT	6.0	5.0	17	11.5	20	23	12	14	**C-WE 08 LL 1/8 NPT X**	1.7
L	315	315	6	1/8-27 NPT	4.0	4.0	19	12.0	20	27	12	14	**C-WE 06 L 1/8 NPT X**	2.1
			6	1/4-18 NPT	4.0	7.0	21	14.0	26	29	12	14	**C-WE 06 L 1/4 NPT X**	2.7
			6	3/8-18 NPT	4.0	8.0	25	18.0	28	33	17	14	**C-WE 06 L 3/8 NPT X**	5.7
			8	1/8-27 NPT	6.0	4.0	21	14.0	26	29	12	17	**C-WE 08 L 1/8 NPT X**	2.7
			8	1/4-18 NPT	6.0	6.0	21	14.0	26	29	12	17	**C-WE 08 L 1/4 NPT X**	2.9
			10	1/4-18 NPT	8.0	7.0	22	15.0	27	30	14	19	**C-WE 10 L 1/4 NPT X**	3.5
			10	3/8-18 NPT	8.0	8.0	24	17.0	28	32	17	19	**C-WE 10 L 3/8 NPT X**	5.4
			12	1/4-18 NPT	10.0	7.0	24	17.0	28	32	17	22	**C-WE 12 L 1/4 NPT X**	4.6
			12	3/8-18 NPT	10.0	8.0	24	17.0	28	32	17	22	**C-WE 12 L 3/8 NPT X**	5.2
			12	1/2-14 NPT	10.0	11.0	28	21.0	34	36	19	22	**C-WE 12 L 1/2 NPT X**	8.8
			15	1/2-14 NPT	12.0	11.0	28	21.0	34	36	19	27	**C-WE 15 L 1/2 NPT X**	9.2
			18	1/2-14 NPT	15.0	12.0	31	23.5	36	40	24	32	**C-WE 18 L 1/2 NPT X**	11.7
	160	160	22	3/4-14 NPT	19.0	16.0	35	27.5	42	44	27	36	**C-WE 22 L 3/4 NPT X**	17.0
			28	1-11 1/2 NPT	24.0	21.0	38	30.5	48	47	36	41	**C-WE 28 L 1 NPT X**	29.0
			35	1 1/4-11 1/2 NPT	30.0	28.0	45	34.5	54	56	41	50	**C-WE 35 L 1 1/4 NPT X**	47.7
			42	1 1/2-11 1/2 NPT	36.0	34.0	51	40.0	61	63	50	60	**C-WE 42 L 1 1/2 NPT X**	70.6
S	630	630	6	1/4-18 NPT	4.0	4.0	23	16.0	26	31	12	17	**C-WE 06 S 1/4 NPT X**	3.8
			8	1/4-18 NPT	5.0	5.0	24	17.0	27	32	14	19	**C-WE 08 S 1/4 NPT X**	4.5
			8	3/8-18 NPT	5.0	8.0	25	18.0	28	33	17	19	**C-WE 08 S 3/8 NPT X**	6.1
			8	1/2-14 NPT	5.0	10.0	30	23.0	34	38	19	19	**C-WE 08 S 1/2 NPT X**	10.9
			10	1/4-18 NPT	7.0	5.0	25	17.5	28	34	17	22	**C-WE 10 S 1/4 NPT X**	6.0
			10	3/8-18 NPT	7.0	7.0	25	17.5	28	34	17	22	**C-WE 10 S 3/8 NPT X**	6.4
			12	1/4-18 NPT	8.0	5.0	29	21.5	28	38	17	24	**C-WE 12 S 1/4 NPT X**	7.5
			12	3/8-18 NPT	8.0	8.0	29	21.5	28	38	17	24	**C-WE 12 S 3/8 NPT X**	7.7
			12	1/2-14 NPT	8.0	10.0	30	22.5	34	39	19	24	**C-WE 12 S 1/2 NPT X**	10.8
			14	1/2-14 NPT	10.0	10.0	30	22.0	34	40	19	27	**C-WE 14 S 1/2 NPT X**	10.6
	400	400	16	1/2-14 NPT	12.0	12.0	33	24.5	36	43	24	30	**C-WE 16 S 1/2 NPT X**	13.3
			20	3/4-14 NPT	16.0	16.0	37	26.5	42	48	27	36	**C-WE 20 S 3/4 NPT X**	19.9
			25	1-11 1/2 NPT	20.0	20.0	42	30.0	48	54	36	46	**C-WE 25 S 1 NPT X**	38.0
			30	1 1/4-11 1/2 NPT	25.0	25.0	49	35.5	54	62	41	50	**C-WE 30 S 1 1/4 NPT X**	60.5
	250	315	38	1 1/2-11 1/2 NPT	32.0	32.0	57	41.0	61	72	50	60	**C-WE 38 S 1 1/2 NPT X**	88.0

*Replace the character "**C**" with "**CF**" when you require steel!
C = Stainless Steel, 1.4571 **CF** = Galvanized Steel Cr(VI)-free

CONEXA www.CONEXA.de Phone: +49 5541 9877 -0 Fax: +49 5541 9877 -77