



C-GE-NPT

Male stud connector (L)

NPT-Male Stud Connector (SAE J476) /
24° Tube Connection (DIN EN ISO 8434-1)







Series	PN [bar] C	PN [bar] CF	ØD1 [mm]	T	ØD3 [mm]	L1 [mm]	L2 [mm]	L3 [mm]	L4 [mm]	S1 [mm]	S2 [mm]	Ordering Code *	kg/ 100
L	315	315	6	1/8-27 NPT	4	24	17.0	10.0	32	12	14	**C-GE 06 L 1/8 NPT X**	1.2
			6	1/4-18 NPT	4	30	23.0	14.5	38	17	14	**C-GE 06 L 1/4 NPT X**	2.8
			6	3/8-18 NPT	4	30	23.0	14.5	38	19	14	**C-GE 06 L 3/8 NPT X**	3.9
			6	1/2-14 NPT	4	36	29.0	19.5	44	22	14	**C-GE 06 L 1/2 NPT X**	5.8
			8	1/8-27 NPT	4	25	18.0	10.0	33	14	17	**C-GE 08 L 1/8 NPT X**	1.6
			8	1/4-18 NPT	6	30	23.0	14.5	38	17	17	**C-GE 08 L 1/4 NPT X**	2.6
			8	3/8-18 NPT	6	30	23.0	14.5	38	19	17	**C-GE 08 L 3/8 NPT X**	3.8
			8	1/2-14 NPT	6	36	29.0	19.5	44	22	17	**C-GE 08 L 1/2 NPT X**	6.9
			10	1/8-27 NPT	4	25	18.0	10.0	33	17	19	**C-GE 10 L 1/8 NPT X**	1.9
			10	1/4-18 NPT	7	31	24.0	14.5	39	17	19	**C-GE 10 L 1/4 NPT X**	2.7
			10	3/8-18 NPT	7	32	25.0	14.5	40	19	19	**C-GE 10 L 3/8 NPT X**	4.1
			10	1/2-14 NPT	8	37	30.0	19.5	45	22	19	**C-GE 10 L 1/2 NPT X**	6.6
			10	3/4-14 NPT	8	38	31.0	19.5	46	30	19	**C-GE 10 L 3/4 NPT X**	12.0
			12	1/8-27 NPT	4	26	19.0	10.0	34	19	22	**C-GE 12 L 1/8 NPT X**	2.4
			12	1/4-18 NPT	7	32	25.0	14.5	40	19	22	**C-GE 12 L 1/4 NPT X**	3.1
			12	3/8-18 NPT	8	32	25.0	14.5	40	19	22	**C-GE 12 L 3/8 NPT X**	3.9
			12	1/2-14 NPT	10	37	30.0	19.5	45	22	22	**C-GE 12 L 1/2 NPT X**	6.4
			15	3/8-18 NPT	8	33	26.0	14.5	41	24	27	**C-GE 15 L 3/8 NPT X**	5.1
			15	1/2-14 NPT	12	38	31.0	19.5	46	24	27	**C-GE 15 L 1/2 NPT X**	6.7
			15	3/4-14 NPT	12	39	32.0	19.5	47	30	27	**C-GE 15 L 3/4 NPT X**	11.4
			15	1-11 1/2 NPT	12	45	38.0	24.5	53	36	27	**C-GE 15 L 1 NPT X**	21.7
			18	3/8-18 NPT	8	34	26.5	14.5	43	27	32	**C-GE 18 L 3/8 NPT X**	7.1
			18	1/2-14 NPT	12	39	31.5	19.5	48	27	32	**C-GE 18 L 1/2 NPT X**	8.1
			18	3/4-14 NPT	15	39	31.5	19.5	48	30	32	**C-GE 18 L 3/4 NPT X**	10.9
			18	1-11 1/2 NPT	15	45	37.5	24.5	54	36	32	**C-GE 18 L 1 NPT X**	20.0
	160	160	22	3/8-18 NPT	8	36	29.0	14.5	45	32	36	**C-GE 22 L 3/8 NPT X**	9.2
			22	1/2-14 NPT	12	41	33.5	19.5	50	32	36	**C-GE 22 L 1/2 NPT X**	10.0
			22	3/4-14 NPT	16	41	33.5	19.5	50	32	36	**C-GE 22 L 3/4 NPT X**	10.9
			22	1-11 1/2 NPT	19	47	39.5	24.5	56	36	36	**C-GE 22 L 1 NPT X**	17.4
			28	3/4-14 NPT	16	42	34.5	19.5	51	41	41	**C-GE 28 L 3/4 NPT X**	15.8
			28	1-11 1/2 NPT	21	47	39.5	24.5	56	41	41	**C-GE 28 L 1 NPT X**	19.7
			28	1 1/4-11 1/2 NPT	24	49	41.5	25.0	58	46	41	**C-GE 28 L 1 1/4 NPT X**	31.4
			35	1-11 1/2 NPT	22	50	39.5	24.5	61	46	50	**C-GE 35 L 1 NPT X**	23.0
			35	1 1/4-11 1/2 NPT	28	51	40.5	25.0	62	46	50	**C-GE 35 L 1 1/4 NPT X**	29.5
			42	1 1/4-11 1/2 NPT	28	53	42.0	25.0	65	55	60	**C-GE 42 L 1 1/4 NPT X**	38.2
			42	1 1/2-11 1/2 NPT	36	53	42.0	26.0	65	55	60	**C-GE 42 L 1 1/2 NPT X**	37.8

*Replace the character "**C**" with "**CF**" when you require steel!
C = Stainless Steel, 1.4571 **CF** = Galvanized Steel Cr(VI)-free

CONEXA
www.CONEXA.de Phone: +49 5541 9877 -0 Fax: +49 5541 9877 -77



C-GE-NPT


Male stud connector (S)


NPT-Male Stud Connector (SAE J476) /
24° Tube Connection (DIN EN ISO 8434-1)



C-GE-UNF/UN







Series	PN [bar] C	PN [bar] CF	ØD1 [mm]	T	ØD3 [mm]	L1 [mm]	L2 [mm]	L3 [mm]	L4 [mm]	S1 [mm]	S2 [mm]	Ordering Code *	kg/ 100
S	630	630	6	1/8-27 NPT	4	28	21.0	10.0	36	14	17	**C-GE 06 S 1/8 NPT X**	2.2
			6	1/4-18 NPT	4	35	28.0	14.5	43	17	17	**C-GE 06 S 1/4 NPT X**	3.8
			6	3/8-18 NPT	4	33	26.0	14.5	41	19	17	**C-GE 06 S 3/8 NPT X**	4.6
			6	1/2-14 NPT	4	42	35.0	19.5	50	22	17	**C-GE 06 S 1/2 NPT X**	7.2
			8	1/4-18 NPT	5	35	28.0	14.5	43	17	19	**C-GE 08 S 1/4 NPT X**	3.9
			8	3/8-18 NPT	5	35	28.0	14.5	43	19	19	**C-GE 08 S 3/8 NPT X**	5.1
			8	1/2-14 NPT	5	42	35.0	19.5	50	22	19	**C-GE 08 S 1/2 NPT X**	9.0
			10	1/4-18 NPT	5	35	27.5	14.5	44	19	22	**C-GE 10 S 1/4 NPT X**	4.4
			10	3/8-18 NPT	7	35	27.5	14.5	44	19	22	**C-GE 10 S 3/8 NPT X**	4.9
			10	1/2-14 NPT	7	42	34.5	19.5	51	22	22	**C-GE 10 S 1/2 NPT X**	8.6
			10	3/4-14 NPT	7	44	36.5	19.5	53	30	22	**C-GE 10 S 3/4 NPT X**	15.6
			12	1/4-18 NPT	5	37	29.5	14.5	46	22	24	**C-GE 12 S 1/4 NPT X**	6.0
			12	3/8-18 NPT	8	37	29.5	14.5	46	22	24	**C-GE 12 S 3/8 NPT X**	6.3
			12	1/2-14 NPT	8	42	34.5	19.5	51	22	24	**C-GE 12 S 1/2 NPT X**	8.5
			12	3/4-14 NPT	8	44	36.5	19.5	53	30	24	**C-GE 12 S 3/4 NPT X**	15.7
			14	3/8-18 NPT	8	39	31.0	14.5	49	24	27	**C-GE 14 S 3/8 NPT X**	7.5
			14	1/2-14 NPT	10	44	36.0	19.5	54	24	27	**C-GE 14 S 1/2 NPT X**	9.1
			14	3/4-14 NPT	10	46	38.0	19.5	56	30	27	**C-GE 14 S 3/4 NPT X**	15.6
			14	1-11 1/2 NPT	10	51	43.0	24.5	61	36	27	**C-GE 14 S 1 NPT X**	26.3
	400	400	16	3/8-18 NPT	8	39	30.5	14.5	49	27	30	**C-GE 16 S 3/8 NPT X**	8.7
			16	1/2-14 NPT	12	48	39.5	19.5	58	32	30	**C-GE 16 S 1/2 NPT X**	9.5
			16	3/4-14 NPT	12	46	37.5	19.5	56	30	30	**C-GE 16 S 3/4 NPT X**	14.7
			16	1-11 1/2 NPT	12	51	42.5	24.5	61	36	30	**C-GE 16 S 1 NPT X**	25.2
			20	1/2-14 NPT	12	48	37.5	19.5	59	32	36	**C-GE 20 S 1/2 NPT X**	14.3
			20	3/4-14 NPT	16	48	37.5	19.5	59	32	36	**C-GE 20 S 3/4 NPT X**	20.3
			20	1-11 1/2 NPT	16	55	44.5	24.5	66	36	36	**C-GE 20 S 1 NPT X**	25.6
			25	3/4-14 NPT	16	52	40.0	19.5	64	41	46	**C-GE 25 S 3/4 NPT X**	24.3
			25	1-11 1/2 NPT	20	57	45.0	24.5	69	41	46	**C-GE 25 S 1 NPT X**	28.6
			25	1 1/4-11 1/2 NPT	20	58	46.0	25.0	70	46	46	**C-GE 25 S 1 1/4 NPT X**	43.3
			25	1 1/2-11 1/2 NPT	20	61	49.0	26.0	73	50	46	**C-GE 25 S 1 1/2 NPT X**	56.3
			30	3/4-14 NPT	16	54	40.5	19.5	67	46	50	**C-GE 30 S 3/4 NPT X**	31.0
			30	1-11 1/2 NPT	20	59	45.5	24.5	72	46	50	**C-GE 30 S 1 NPT X**	34.7
			30	1 1/4-11 1/2 NPT	25	60	46.5	25.0	73	46	50	**C-GE 30 S 1 1/4 NPT X**	39.9
			30	1 1/2-11 1/2 NPT	25	60	46.5	26.0	73	50	50	**C-GE 30 S 1 1/2 NPT X**	50.1
	250	315	38	1-11 1/2 NPT	22	64	48.0	24.5	79	55	60	**C-GE 38 S 1 NPT X**	52.0
			38	1 1/4-11 1/2 NPT	25	65	49.0	25.0	80	55	60	**C-GE 38 S 1 1/4 NPT X**	61.0
			38	1 1/2-11 1/2 NPT	32	65	49.0	26.0	80	55	60	**C-GE 38 S 1 1/2 NPT X**	57.5

*Replace the character "**C**" with "**CF**" when you require steel!
C = Stainless Steel, 1.4571 **CF** = Galvanized Steel Cr(VI)-free

CONEXA www.CONEXA.de Phone: +49 5541 9877 -0 Fax: +49 5541 9877 -77