VIME® INDUSTRIAL
The Quality is Transparent

EPH FN

EPH FN PLANETARY WINCHES

Models EPH FN are hydraulic planetary winches, designed for long life, offer best safe duty.
These winches are built according with higher safety standards in compliance with Directive Machinery 2006/42/CE Harmonized EN 14492-1. The high efficiency planetary gear train, assures fast payout and rewind winching operation. The innovative brake system makes these winches reliable and great for industrial applications.

FEATURES

- ❏ **COMPACT**
  Hardened steel single stage planetary gear train
- ❏ **FAST WINCHING SPEED**
  Fast payout and rewind
- ❏ **VERSATILE MOUNTING**
  Designed for either foot or side mounting
- ❏ **LIGHT AND STRONG**
  Body manufactured from hardened special aluminum castings, which reduces weight and increases strength
  Powder coat finished
- ❏ **MULTI-DISC PRESSURE RELEASED BRAKE**
  Gives a reliable and effective full brake capacity
- ❏ **DRUM SIZE AVAILABLE**
  Standard 252 mm (9.9 inch) EPH 6200FN - EPH 6700FN
- ❏ **TOTALLY OIL COOLED**
  Gears and brake are bathed in oil for maximum performance, quiet operation and to extend internal components life span

ACCESSORIES :


- ❏ Zinc plated Heavy-duty roller fairlead
- ❏ Zinc plated Cable tensioner
- ❏ Air clutch shifter - drum free spooling

PLANETARY

CE
EN 14492-1

EPH 6200FN

PULLING CAPACITY	6.200 Kgs	[13.650 Lbs]
WORKING PRESSURE	155 Bar	[2,248 Psi]
WIRE ROPE DIA.	12 mm	[- -]
MAX. ROPE CAPACITY	39 Mt	[128,0 Ft]
MAX. SPEED LINE (first layer)	9,2 Mt/Min	[30,2 Ft]
MAX. OIL SUPPLY	60 Lt/Min	[15,85 GPM]




PLANETARY

CE
EN 14492-1

EPH 6700FN

PULLING CAPACITY	6.700 Kgs	[14.770 Lbs]
WORKING PRESSURE	165 Bar	[2,393 Psi]
WIRE ROPE DIA.	12 mm	[- -]
MAX. ROPE CAPACITY	39 Mt	[128,0 Ft]
MAX. SPEED LINE (first layer)	9,2 Mt/Min	[30,2 Ft]
MAX. OIL SUPPLY	60 Lt/Min	[15,85 GPM]



WARNING
Do not use winch to lift support or transport personnel.

© copyright V.I.M.E. srl