

RELIEF VALVE
(Pilot Operated Balanced Piston)

Ordering Code:	**RP-16A-X-Y-Z**



UNIT:mm


Illustrations / detail are for reference only. Data subject to change.



TECHNICAL DATA

Max. Operating pressure: 350		bar
Rated flow:	380	l/min
Cavity-Tooling:	16A-2	
Installation torque:	200 - 215	Nm
Weight:	0.53 (**Z**=L)	kg




Port② is rated for full pressure. For cross-relief circuit applications, please account for spool internal leakage and **consult the Winner sales department for guidance.** If your application requires rapid response and ultra-low leakage, please refer to our RD Series.



X	OPERATION	
20	① to ② (P to T)	

- Response Time-Typical (10 ms)
- Maximum Leakage Approximately (66 cc/min./70 bar)

Y	SPRINGS	
	ADJUSTMENT RANGES	
A	7 - 210 bar (70 bar Standard Setting)	
B	3.5 - 105 bar (70 bar Standard Setting)	
C	10.5 - 420 bar (70 bar Standard Setting)	
D	1.7 - 55 bar (28 bar Standard Setting)	
E	1.7 - 28 bar (14 bar Standard Setting)	
N	4 - 55 bar (28 bar Standard Setting)	
Q	4 - 28 bar (14 bar Standard Setting)	
W	10.5 - 315 bar (70 bar Standard Setting)	

Z	OPTIONS		
L	Leakproof hex. socket screw.		
LP	Leakproof hex. socket screw. With stainless steel external metal components		
K	Handknob with Lock Knob. (Order Code: 6ZAK001)		
C	Stainless Steel Tamper Resistant Cover.	