POWER UNITS ORDERING GUIDANCE

YBZ □ (1)(2) - □□□□□□□ (3)(4)(5)(6)(7)(8) / □□□□□□ (9)(10)(11)(12)(13)(14)

(1) Product name:hydraulic power units

(2) Series No.,which would be changed once there comes big improvement of the whole.power units.It comes into 1,2,3,4. Especially,the No.5 represents manifold made of aluminium. the No.6 represents manifold made of die-casting aluminium.

(3) System pressure, which is used to point out the preset pressure of the relief valve.
A-1.6MPa B-2.5MPa C-6.3MPa D-10MPa E-16MPa F-20MPa G-25MPa H-32MPa

(4) Rated pump displacement
①CBK series pumps;
0.63ml/r 0.8ml/r 1.2ml/r 1.6ml/r 2.1ml/r 2.5ml/r 2.7ml/r 3.2ml/r 3.7ml/r 4.2ml/r 5ml/r 6ml/r 8ml/r
②CBG series pumps;
2ml/r 3ml/r 3.5ml/r 4ml/r
③CBE series pumps
0.26ml/r 0.32ml/r 0.38ml/r 0.5ml/r 0.63ml/r 0.88ml/r 1.00ml/r 1.25ml/r 1.5ml/r

(5) Oil tank capacity
U—0.5L V—0.8L W—1.0L S—1.4L Y—1.5L Z—2.0L A—3.0L or 4.0L B—5L or 6L C—8.0L D—10L
E—12L F—14L G—16L H—20L I—22L J—25L K—35L L—50L M-60L N—70L P—80L Q—13L R—30L S—7L
X-2.5L T-100L TA-120L

(6) Motor voltage
①DC motor: 1-12V 2-24V 9-48V 10-72V 12-60V
②AC motor: 3—220V 4—380V 5—110V 6—415V 7—230/460V 8—115/230V 11—200V
13-110/220V 14-220/380V 15-230/400V 16-460V 17-400V 18-240V 19-120V 20-190/208-240/380V/460
21-230V 22-440V 23-100V 24-230/460/575V 25-208/230/460/380/400V 26-277V 27-220/44V 28-575V

(7) Motor power
①DC motor:X—0.25kw S—0.5kw T—0.8kw U—1.0kw V— 1.2kw W—1.5kw A—2.0kw M-2.2kw
N-2.5kw L-1.8kw B—3.0kw P-4.0kw
② AC motor:C—0.37kw D—0.55kw E—0.75kw F—1.1kw G— 1.5kw H—2.2kw I—3.0kw J—4.0kw
Q-0.85kw R-1.8kw K-3.7kw

(8) Hydraulic circuit No.See the hydraulic schematic circuit in the detailed page.

(9) Motor type
O—no motor
T—the motor with Special requirements
①AC motors
A—Steel housing, vertical & horizontal,9T Spline,the center distance of the mounting hole is 113x113.
B—Steel housing, vertical,9T Spline,the center distance of the mounting hole is 113x113.
G—Extruding aluminum housing. vertical & horizontal,Tang,the center distance of the mounting hole is 113x113.
H—Extruding aluminum housing. vertical,Tang,the center distance of the mounting hole is 113x113.
L—Casting aluminium housing. vertical & horizontal, 9T Spline,the center distance of the mounting hole is 113x113.
M—Casting aluminium housing. vertical,9T Spline,the center distance of the mounting hole is 113x113.
N—Casting aluminium housing. vertical & horizontal,Tang,the center distance of the mounting hole is 117.4x117.4.
② DC motors

POWER UNITS ORDERING GUIDANCE

U—3 " DC motor(0.34HP-1.1HP)
V—3.5 " DC motor(1.1HP-1.6HP)
W—4.5 " DC motor(2HP-3HP)
X—5 " DC motor(4HP)

(10) Motor speed
O—Hydraulic system in the non-motor
T—the motor with Special requirements
①50HZ AC motor,50HZ A—960rpm B—1450rpm C—2850rpm D—1450/2850rpm
②60HZ AC motor,60HZ J—1100rpm K—1750rpm L—3450rpm
③50HZ/60HZ M-50HZ/60HZ N-50HZ/60HZ
④DC motor U—2500rpm V—3500rpm W—4500rpm

(11) ank appearance
A—neck i.d φ120, steel, round, horizontal.
B—neck i.d φ120, steel, round, vertical.
C—neck i.d φ120, steel, square, horizontal.
D—neck i.d φ120, steel, square, vertical.
E—neck i.d φ138, steel, round, horizontal.
F—neck i.d φ138, stee, round, vertical.
G—neck i.d φ138, steel, square, horizontal.
H—neck i.d φ138, stee, square, vertical.
J—neck i.d φ94, steel, round, horizontal.
K—neck i.d φ94, steel, round, vertical.
L—neck i.d φ94, steel, square, horizontal.
M—neck i.d φ94,steel, square, vertical.
N—neck i.d φ120, steel, round,200
P—neck i.d φ120,blow-molded plastic, round, horizontal.
Q—neck i.d φ120,blow-molded plastic, round, vertical.
R—neck i.d φ73, steel, square, horizontal.
S—neck i.d φ73, steel, square, vertical.
U—neck i.d φ120,injection molded plastic, round, horizontal.
V—neck i.d φ120,injection molded plastic, round, vertical.
O—non-tank
T—the tank with Special requirements.

(12) Solenoid valve volt
A—12VDC,without manual override function.
B—24VDC,without manual override function.
C—24VAC,without manual override function.
D—110VAC,without manual override function.
E—220VAC,without manual override function.
H—12VDC,with manual override function.
I—24VDC,with manual override function.
J—24VAC,with manual override function.
K—110VAC,with manual override function.
L—220VAC,with manual override function.
O—No solenoid valve.
T—The solenoid valve with special requirements.
Z—referring to the manual valve with micro switch.

(13) Manifold model is selected by manufacturer.

(14) Design No. which is selected by manufacturer,may be 1,2,3 or A,B,C.