

Technical data E


- Interchange: exclusive Dnp profile
- Occlusion: flat face
- Locking: lever with safety device
- Material: steel and aluminum
- Finishing: Zn-Fe (Cr III), Anodizing
- Threads: BSP-NPT-SAE-METRICS-Rc
- Standard seals: NBR and PU
- Working temperature: -25°C+100°C
- Optional seals: FKM,EPDM or more
- Working pressure: 350 bar
- Connection under residual pressure: allowed (male side only)

Technische Merkmale D


- Austauschbarkeit: laut exclusive Dnp Zeichnung
- Verschluss: flachdichtend
- Kupplung: Hebel mit doppelter Sicherung
- Werkstoff: Stahl und Aluminium
- Ausführung: Zn-Fe (Cr III), Eloxiert
- Gewinde: BSP-NPT-SAE-METRIC-Rc
- Standard-Dichtungen: NBR und PU
- Betriebstemperatur: -25°C+100°C
- Dichtungen nach Wahl: FKM,EPDM,usw.
- Betriebsdruck: 350 bar
- Kuppeln unter Restdruck: erlaubt (nur Steckerseite)


Nominal size				Max working pressure	Rated flow	Max flow rate	Min burst pressure			Fluid spillage
							Male	Female	Coupled	
DNP	BG	ISO	Ømm	MPa	l/min	l/min	MPa	MPa	MPa	cc
13	2	10	8.6	35	23	46	140	140	140	0.010


1 MPa = 145.04 psi • 1 l = 0.264 gal




PSQ2 DIMENSION









PSQ2 FIXED




THREADS	DNP	BG	ISO	Housings	No. of Couplings	F	STANDARD	FIXED PART	
								CODE	Weight (g)
IG 1	13	2	10	2	2	BSP 1/4"	DIN 3852-2	PSQ2.1306.002	1380
	13	2	10	2	2	NPT 1/4"	ANSI B1.20.1	PSQ2.1306.012	1380
	13	2	10	2	2	BSP 3/8"	DIN 3852-2	PSQ2.1310.002	1360
	13	2	10	2	2	NPT 3/8"	ANSI B1.20.1	PSQ2.1310.012	1360
	13	2	10	2	2	Rc 3/8"	EN 10226-2	PSQ2.1310.042	1360
	13	2	10	2	2	BSP 1/2"	DIN 3852-2	PSQ2.1313.002	1330
	13	2	10	2	2	NPT 1/2"	ANSI B1.20.1	PSQ2.1313.012	1335
	13	2	10	2	2	Rc 1/2"	EN 10226-2	PSQ2.1313.042	1340
	13	2	10	2	2	M16x1.5	DIN 3852-1	PSQ2.1316.102	1365
	13	2	10	2	2	M18x1.5	DIN 3852-1	PSQ2.1318.102	1350
IG 2	13	2	10	2	2	9/16"-18 UNF 2B	SAE J 1926-1	PSQ2.1315.032	1355
	13	2	10	2	2	3/4"-16 UNF 2B	SAE J 1926-1	PSQ2.1319.032	1340
	13	2	10	2	2	M22x1.5	ISO 6149-1	PSQ2.1322.102	1325
AG 3	13	2	10	2	2	M18x1.5-12L	ISO 8434-1-L	PSQ2.1318.302	1300
	13	2	10	2	2	M20x1.5-12S	ISO 8434-1-S	PSQ2.1320.402	1315
	13	2	10	2	2	M22x1.5-15L	ISO 8434-1-L	PSQ2.1322.302	1310
AG 8	13	2	10	2	2	BSP 1/2"	BS B5200	PSQ2.1313.702	1305

PSQ2 MOBILE



THREADS	DNP	BG	ISO	Housings	No. of Couplings	F	STANDARD	MOBILE PART	
								CODE	Weight (g)
IG 1	13	2	10	2	2	BSP 1/4"	DIN 3852-2	PSQ2.1306.003	2345
	13	2	10	2	2	NPT 1/4"	ANSI B1.20.1	PSQ2.1306.013	2360
	13	2	10	2	2	BSP 3/8"	DIN 3852-2	PSQ2.1310.003	2325
	13	2	10	2	2	NPT 3/8"	ANSI B1.20.1	PSQ2.1310.013	2355
	13	2	10	2	2	Rc 3/8"	EN 10226-2	PSQ2.1310.043	2365
	13	2	10	2	2	BSP 1/2"	DIN 3852-2	PSQ2.1313.003	2295
	13	2	10	2	2	NPT 1/2"	ANSI B1.20.1	PSQ2.1313.013	2330
	13	2	10	2	2	Rc 1/2"	EN 10226-2	PSQ2.1313.043	2335
	13	2	10	2	2	M16x1.5	DIN 3852-1	PSQ2.1316.103	2330
	13	2	10	2	2	M18x1.5	DIN 3852-1	PSQ2.1318.103	2320
IG 2	13	2	10	2	2	9/16"-18 UNF 2B	SAE J 1926-1	PSQ2.1315.033	2350
	13	2	10	2	2	3/4"-16 UNF 2B	SAE J 1926-1	PSQ2.1319.033	2315
	13	2	10	2	2	M22x1.5	ISO 6149-1	PSQ2.1322.103	2305
AG 3	13	2	10	2	2	M18x1.5-12L	ISO 8434-1-L	PSQ2.1318.303	2310
	13	2	10	2	2	M20x1.5-12S	ISO 8434-1-S	PSQ2.1320.403	2315
	13	2	10	2	2	M22x1.5-15L	ISO 8434-1-L	PSQ2.1322.303	2310
AG 8	13	2	10	2	2	BSP 1/2"	BS B5200	PSQ2.1313.703	2270


THREADS



IG 1 IG 2 AG 3 AG 8


SPARE PARTS FIXED PLATE PSQ2

POS.	PART NUMBER	WEIGHT (g)
1	PSQ.220.100	697
2	PSQ.KIT.020	64
3	PSQ.KIT.017	106
4	PSQ.000.016	2
5	SEE SPARE PARTS ISO 10	




SPARE PARTS MOBILE PLATE PSQ2

POS.	PART NUMBER	WEIGHT (g)
6	PSQ.320.300	524
7	PSQ.KIT.011	51
8	PSQ.KIT.050	43
9	PSQ.KIT.042	1155
10	PSQ.000.022	70
11	SEE SPARE PARTS ISO 10	




SPARE PARTS ISO 10 COUPLINGS




THREADS	DNP	BG	ISO	L2	L3	L4	ØT	F	STANDARD	SPARE PARTS			
										FEMALE - MUFFE		MALE - STECKER	
										COD. F	Weight (g)	COD. M	Weight (g)
IG 1	13	2	10	73.5	74			BSP 1/4"	DIN 3852-2	POT4.1306.112	270	POT4.1306.113	255
	13	2	10	73.5	75			NPT 1/4"	ANSI B1.20.1	POT4.1306.012	277	POT4.1306.013	262
	13	2	10	73.5	74			BSP 3/8"	DIN 3852-2	POT4.1310.112	261	POT4.1310.113	245
	13	2	10	73.5	77.5			NPT 3/8"	ANSI B1.20.1	POT4.1310.012	263	POT4.1310.013	261
	13	2	10	73.5	77.5			Rc 3/8"	EN 10226-2	POT4.1310.042	262	POT4.1310.043	264
	13	2	10	73.5	74			BSP 1/2"	DIN 3852-2	POT4.1313.112	246	POT4.1313.113	231
	13	2	10	73.5	78			NPT 1/2"	ANSI B1.20.1	POT4.1313.012	248	POT4.1313.013	248
	13	2	10	74.5	78			Rc 1/2"	EN 10226-2	POT4.1313.042	252	POT4.1313.043	249
	13	2	10	73.5	74			M16x1.5	DIN 3852-1	POT4.1316.102	263	POT4.1316.103	248
	13	2	10	73.5	74			M18x1.5	DIN 3852-1	POT4.1318.102	256	POT4.1318.103	241
IG 2	13	2	10	72	75			9/16"-18 UNF 2B	SAE J1926-1	POT4.1315.032	260	POT4.1315.033	256
	13	2	10	73.5	75			3/4"-16 UNF 2B	SAE J1926-1	POT4.1319.032	253	POT4.1319.033	240
	13	2	10	74.5	75			M22x1.5	ISO 6149-1	POT4.1322.102	244	POT4.1322.103	235
AG 3	13	2	10	73.5	78	11	12L	M18x1.5	ISO 8434-1-L	POT4.1318.302	231	POT4.1318.303	238
	13	2	10	74.5	78	12	15L	M22x1.5	ISO 8434-1-L	POT4.1322.302	237	POT4.1322.303	238
	13	2	10	74.5	78	12	12S	M20x1.5	ISO 8434-1-S	POT4.1320.402	239	POT4.1320.403	241
AG 8	13	2	10	75	75	13		BSP 1/2"	BS B5200	POT4.1313.702	235	POT4.1313.703	216

SPARE PARTS SEALS



NOMINAL SIZE			MALE GASKET
DNP	BG	ISO	PU(POLYURETHANE)
13	2	10	PLK.013.210

THREADS



IG 1 IG 2 AG 3 AG 8

DOCKING STATION

POS.	PART NUMBER	WEIGHT (g)
1	PPSQ.220	740




PLATE CAP

POS.	PART NUMBER	WEIGHT (g)
1	SPSQ.220	180

