
DIRECTIONAL CONTROL VALVES CETOP 3/NG6



CETOP 3/NG06

STANDARD SPOOLS	SECT. A	12
AD3E...	SECT. A	13
AD3E...*S	SECT. A	14
AD3E...KJ	SECT. A	15
AD3V...	SECT. A	16
AD3L...	SECT. A	17
OTHER OPERATOR	SECT. A	18
AD3P...	SECT. A	19
AD3O...	SECT. A	19
AD3M...	SECT. A	20
AD3D...	SECT. A	20
"D15" DC COILS	SECT. A	21
"B14" AC SOLENOIDS	SECT. A	21
STANDARD CONNECTORS	SECT. L	15
"LE" VARIANTS	SECT. A	22
L.V.D.T.	SECT. A	23
MICROSWITCH	SECT. A	24

INTRODUCTION

The directional control valves NG6 are designed for subplate mounting with an interface in accordance with UNI ISO 4401 - 03 - 02 - 0 - 94 standard (ex CETOP R 35 H 4.2-4-03), and can be used in all fields on account of their high flow rate and pressure capacities combined with compact overall dimensions.

The use of solenoids with wet armatures allows a very practical, safe construction completely dispensing with dynamic seals; the solenoid tube is screwed directly onto the valve chest whilst the coil is kept in position by means of a lock nut.

The special, precise construction of the ports and the improvement of the spools enables relatively high flow rates to be accommodated with a minimal pressure drop (Δp).
The operation of the directional valves may be electrical, pneumatic, oleodynamic, mechanical or lever.


The centre position is obtained by means of calibrated length springs which reposition the spool in the centre or end of travel position once the action of the impulse is over.

The solenoids are constructed with a protection class of IP66 to DIN 40050 standards and are available in either AC or DC form in different voltage and frequencies.
The new type DC coil "D15", of cause their high performance, allows to increasing the limits of use respect to last series.
All types of electrical control are available, on request, with different types of manual emergency controls.

The solenoid coils are normally arranged for DIN 43650 ISO 4400 type connectors; is available on request these variant coils: with AMP Junior connections, with AMP junior and integrated diode, with Deutsch DT04-2P connections or solenoid with flying leads. Connectors with built in rectifiers or pilot lights are also available.

The valves are designed for use with DIN 51524 standard hydraulic mineral oils and it is recommended that filters should be fitted to ensure a maximum contamination level of class 10 in accordance with NAS 1638, $ß_{25} \geq 75$.

PRESSURE DROPS



The diagram at the side shows the pressure drop curves for spools during normal usage. The fluid used is a mineral oil with a viscosity of 46 mm^2/s at 40°C; the tests have been carried out at a fluid temperature of 40°C. For higher flow rates than those in the diagram, the losses will be those expressed by the following formula:

$$\Delta p1 = \Delta p \times (Q1/Q)^2$$

where Δp will be the value for the losses for a specific flow rate Q which can be obtained from the diagram, Δp1 will be the value of the losses for the flow rate Q1 that is used.

Spool type	Connections				
	P→A	P→B	A→T	B→T	P→T
01	5	5	5	5	
02	7	7	7	7	6
03	5	5	6	6	
04	2	2	2	2	4
44	1	1	2	2	3
05	7	7	5	5	
06	5	5	7	5	
66	5	5	5	7	
07		2	6		
08	6	6			
09		5		5	
	Curve No.				

Spool type	Connections				
	P→A	P→B	A→T	B→T	P→T
10	5	5	5	5	
11	5			5	
22		5	5		
12		5		6	
13		5	6	6	
14	4	3	3	3	4
28	3	4	3	3	4
15-19*	5	5	6	6	
16	5	5	4	4	
17-21*	3	4			
20*	4	4	4	4	
	Curve No.				

(*) Value with energized solenoid

ORDERING CODE

AD	Directional valve
3	CETOP 3/NG6
E	Type of operator For other operator see next pages
**	Spool see page SECT. A 12
*	Mounting type (table 1)
*	Voltage (table 2)
**	Variants (table 3)
*	Serial No.

3 = Standard
4 = Only for RS - R6 - KJ - 7J variants

TAB.2 - VOLTAGE

AC SOLENOID B14 **

A	24V/50-60 Hz
B	48V/50-60 Hz*
J	115V/50Hz - 120V/60Hz
Y	230V/50Hz - 240V/60Hz
K	AC without coils

Other voltages available on request.

DC COIL D15 (30W) **

L	12V	
M	24V	115Vac/50Hz 120Vac/60Hz with rectifier
V	28V*	
N	48V*	
Z	102V*	230Vac/50Hz 240Vac/60Hz with rectifier
P	110V*	
X	205V*	
W	DC without coils	


• AMP Junior coils (with or without diode) and coils with flying leads and coils type Deutsch, are available in 12V or 24V DC voltage only.

• The coil with eCoat protection (RS variant) is available in 12V, 24V, 28V or 110V DC voltage only.

* Voltage available upon request
** Technical data see page Sect. A 21

TAB.1- MOUNTING

STANDARD

C 

D 

E 

F 

SPECIALS

G 

H 

I 

L 

M 

• **Mounting type D** is only for valves with detent

• In case of **mounting D** with detent a maximum supply time of 2 sec is needed (only for AC coils).

A

TAB.3 - VARIANTS

VARIANT	CODE	♦	PAGE
No variant (without connectors)	S1(*)		
FKM	SV (*)		
Emergency control lever for directional control valves type ADC3 and AD3E	LE-LF-AX-CE(*)	♦	Sect. A 22
Emergency button	ES(*)		Sect. A 21
Rotary emergency button	P2(*)		Sect. A 21
Rotary emergency button (180°)	R5(*)		Sect. A 21
Preset for microswitch (E/F/G/H mounting only) (see below note ◊)	MS(*)	♦	Sect. A 13 - Sect. A 17
5 micron clearance	SQ(*) (1)	♦	
Spool movement speed control (only VDC) with ø 0.3 mm orifice	3S(*) (1)	♦	Sect. A 14
Spool movement speed control (only VDC) with ø 0.4 mm orifice	JS(*) (1)	♦	Sect. A 14
Spool movement speed control (only VDC) with ø 0.5 mm orifice	5S(*) (1)	♦	Sect. A 14
Spool movement speed control (only VDC) with ø 0.6 mm orifice	6S(*) (1)	♦	Sect. A 14
AMP Junior coil - for12V or 24V DC voltage only	AJ(*)		Sect. A 21
AMP Junior coil and integrated diode - for12V or 24V DC voltage only	AD(*) (1)		Sect. A 21
Coil with flying leads (175 mm) - for12V or 24V DC voltage only	SL (1)		Sect. A 21
Hirschmann coil eCoat surface treatment - for 12V, 24V, 28V or 110V DC voltage only	RS(*)		Sect. A 21
Deutsch DT04-2P connection eCoat surface treatment - for 12V, 24V DC voltage only	R6		Sect. A 21
High corrosion resistance valve - Hirschmann connector	KJ (1)		Sect. A 15
High corrosion resistance valve - Deutsch DT04-2P connector - for 12V, 24V DC voltage only	7J (1)		Sect. A 15
Deutsch DT04-2P coil - for12V or 24V DC voltage only	CZ		Sect. A 21


















Other variants available on request.

◊ = Maximum counter-pressure on T port: 8 bar - Microswitch type MK code 1319098 must be ordered separately.
♦ = Variant codes stamped on the plate


(*) Coils with Hirschmann and AMP Junior connection supplied without connectors. The connectors can be ordered separately, Sect. L 15.
(1) Upon request

DIRECTIONAL CONTROL VALVES
STANDARD SPOOLS CETOP 3/NG6

TWO SOLENOIDS, SPRING CENTRED "C" MOUNTING

Spool type		Covering	Transient position
01		+	
02		-	
03		+	
04		-	
44		-	
05 (1)		+	
66 (1)		+	
06 (1)		+	
07 (1)		+	
08 (1)		+	
09 (1)		+	
10 (1)		+	
22		+	
11 (1)		+	
12 (1)		+	
13 (1)		+	
14 (1)		-	
28 (1)		-	

ONE SOLENOID, SIDE A "E" MOUNTING

Spool type		Covering	Transient position
01		+	
02		-	
03		+	
04		-	
44		-	
05 (1)		+	
66 (1)		+	
06 (1)		+	
08 (1)		+	
10 (1)		+	
12 (1)		+	
15		-	
16		+	
17 (1)		+	
14 (1)		-	
28 (1)		-	

NOTE

(1) Upon request


- With spools **15** / **16** / **17** only mounting **E** / **F** are possible
- **16 / 19** / **20** / **21** spool not planned for **AD3E...*S**
- For lever operated the spools used are different.
Available spools for this kind of valve see AD3L..

ONE SOLENOID, SIDE B "F" MOUNTING

Spool type		Covering	Transient position
01		+	
02		-	
03		+	
04		-	
44		-	
05 (1)		+	
66 (1)		+	
06 (1)		+	
08 (1)		+	
09 (1)		+	
10 (1)		+	
22 (1)		+	
12 (1)		+	
13 (1)		+	
07 (1)		+	
15		-	
16		+	
17 (1)		+	
14 (1)		-	
28 (1)		-	

TWO SOLENOIDS "D" MOUNTING

Spool type		Covering	Transient position
19		-	
20		+	
21 (1)		+	



A max. counter-pressure of 8 bar at T is permitted for the variant with a microswitch (**MS**).
(1) Dynamic pressure allowed on P for 1 million of cycles.
(2) DC: Dynamic pressure allowed for 2 millions of cycles.
AC: Dynamic pressure allowed for 350.000 of cycles.
For dynamic pressure of 100 bar are allowed 1 milion cycles.

Max. pressure port P/A/B (1)	350 bar
Max. pressure port T (for DC) (2)	250 bar
Max. pressure port T (for AC) (2)	160 bar
Max. flow	80 l/min
Max. excitation frequency	3 Hz
Duty cycle	100% ED
Fluid viscosity	10 ÷ 500 mm²/s
Fluid temperature	-25°C ÷ 75°C
Ambient temperature	- 25°C ÷ 60°C
Max. contamination level	class 10 in accordance with NAS 1638 with filter $\beta_{25} \geq 75$
Weight with one DC solenoid	1,65 Kg
Weight with two DC solenoids	2 Kg
Weight with one AC solenoid	1,31 Kg
Weight with two AC solenoids	1,72 Kg

CALIBRATED DIAPHRAGMS (3)


Ø mm	Code
blind	M52.05.0023/4
0.5	M52.05.0023/1
0.6	M52.05.0023/6
0.7	M52.05.0023/8
0.8	M52.05.0023
1.0	M52.05.0023/2
1.2	M52.05.0023/3
1.5	M52.05.0023/7
2.0	M52.05.0023/10
2.2	M52.05.0023/9
2.5	M52.05.0023/5

(3) For high differential pressure please contact our technical department.


OVERALL DIMENSIONS

E = Manual override

MS = Microswitch



Support plane specifications



Fixing screws ISO 4762 M5x30
with material specifications min. 8.8
Tightening torque 5 Nm / 0.5 Kgm

LIMITS OF USE (MOUNTING C-E-F)


The tests have been carried out with solenoids at operating temperature and a voltage 10% less than rated voltage with a fluid temperature of 40°C. The fluid used was a mineral oil with a viscosity of 46 mm²/s at 40°C. The values in the diagram refers to tests carried out with the oil flow in two directions simultaneously T = 2 bar (e.g.. from P to A and the same time B to T). In the case where valves 4/2 and 4/3 were used with the flow in one direction only, the limits of use could have variations which may even be negative. Rest times: the values are indicative and depend on following parameters: hydraulic circuit, fluid used and variations in hydraulic scales (pressure P, flow Q, temperature T). The limit of use for AC solenoids were detected with 50 Hz power.

Direct current: Energizing 30 ÷ 50 ms. De-energizing 10 ÷ 30 ms.

Alternating current: Energizing 8 ÷ 30 ms. De-energizing 15 ÷ 55 ms.


NOTE: The operating limits shown are valid for mountings C, E, F.


DIRECT CURRENT SOLENOIDS (DC)



Spool type	Solenoids DC	Solenoids AC
01	1	9
02	1	9
03	3	10
04	2	15
44	1	9
05	1	16
06-66	5	13
11-22	4	17
14-28	7	12
15	8	14
16	6	11
	Curves	

ALTERNATING CURRENT SOLENOIDS (AC)





"D15" DC COILS

Type of protection (in relation to the connector used)	IP 66
Number of cycles	18.000/h
Supply tolerance	±10%
Ambient temperature	-25°C ÷ 60°C
Duty cycle	100% ED
Insulation class wire	H
Weight	0,354 Kg


- AMP Junior coils (with or without diode) and coils with flying leads and coils type Deutsch, are available in 12V or 24V DC voltage only.
- The pastic type coil (RS variant) is available in 12V, 24V, 28V or 110V DC voltage only.

VOLTAGE (V)	MAX WINDING TEMPERATURE (AMBIENT TEMPERATURE 25°C)	RATED POWER (W)	RESISTANCE AT 20°C (OHM) ±10%
12V	110°C	30	4.8
24V	110°C	30	18.8
28V*	110°C	30	25.6
48V*	110°C	30	75.2
102V(*)(**)	110°C	30	340
110V(*)(**)	110°C	30	387
205V(*)(**)	110°C	30	1375


* Special voltages

** The european low voltage directive is applied to electronical equipments used at a nominal voltages between 50 and 1000 VAC or 75 and 1500 VDC. In conformity with the low directive each part of the manifold or the subplate on which the valve is mounted should be connected to a protective earth with a resistence less than 0.1 ohms.


ECOAT COIL (RS)




EMERG. HIRSCHMANN CONN. MANUAL WITHOUT CONN. (ES)




FLYING LEADS (SL)



AMP JUNIOR (AJ) AJ + DIODE (AD)




DEUTSCH DT04 - 2P (CZ) CZ + ECOAT (R6)





EMERGENCY (COILS WITH HIRSCHMANN CONNECTION)

ROTARY WITHOUT CONNECTOR (P2)



ROTARY 180° WITHOUT CONNECTOR (R5)





"B14" AC SOLENOIDS


Type of protection (in relation to the connector used)	IP 65
Number of cycles	18.000/h
Supply tolerance	+10% / -10%
Ambient temperature	-30°C ÷ 60°C
Duty cycle	100% ED
Insulation class wire	H
Weight	0,436 Kg

VOLTAGE (V)	MAX. WINDING TEMPERATURE (AMBIENT TEMPERATURE 25°C)	RESISTANCE AT 20°C (OHM) ±10%	RATED POWER. (VA)	PICKUP CURRENT (A)
24V/50Hz - 24V/60Hz	100°C - 96°C	1.7	54 - 40	5.6 - 5
48V/50Hz - 48V/60Hz	112°C - 98°C	6.8	45 - 34	5.3 - 5
115V/50Hz - 120V/60Hz *	133°C - 101°C	32.5	61 - 51	3.2 - 3.2
230V/50Hz - 240V/60Hz *	120°C - 103°C	134	62 - 52	1.6 - 1.6


* The european low voltage directive is applied to electronical equipments used at a nominal voltages between 50 and 1000 VAC or 75 and 1500 VDC. In conformity with the low directive each part of the manifold or the subplate on which the valve is mounted should be connected to a protective earth with a resistence less than 0.1 ohms.


EMERGENCY (COILS WITH HIRSCHMANN CONNECTION)

MANUAL WITHOUT CONNECTOR (ES)



ROTARY WITHOUT CONNECTOR (P2)





VARIANTS (*) - EMERGENCY CONTROL LEVER FOR DIRECTIONAL CONTROL VALVES (ADC/AD3E)

The emergency control lever for solenoid valves, represents a develop in terms of safety and flexibility among applied hydraulic components.
Thanks to his flexibility, the component was designed to be inserted between the valve body and the spool, providing total interchangeability between the different types of solenoid body valves. It is compatible with the standard CETOP 3 and stackable valves with threaded connections –G3/8" or 9/16-18UNF (SAE 6). The component is available for both directional control and proportional valves (for the last type of control please contact our Technical Department)
As an emergency lever applied to solenoid valves, the control can be used as a safety device in conformity with the industry standards , also playing an useful role in the event of power cuts. The control can be used in agricultural and mobile fields; the manual action can be used to carry out periodic maintenance work on mobile components of the vehicle , in perfectly safe working conditions.

A

(*) VARIANTS

Variant	Description
LE	Standard coil with Hirschmann connection or without coil (W voltage)
LF	Standard coil without Hirschmann connection(*)
AX	AMP Junior coil(*)
CE	Deutsch coil

Other variants available on request.

(*) Coils with Hirschmann and AMP Junior connection supplied without connectors. The connectors can be ordered separately, Sect. L 15.

Max operating pressure port T:	
dynamic	160 bar
static	210 bar
Max operating pressure port P for series connection configuration	160 bar

- **MOUNTING TYPE: C / F / H**
- **SPOOLS TYPE: 01/02/03*/04/16/17/66**

HYDRAULIC SIMBOL




* The spool 03 is allowed only on AD3E. Not permitted with ADC3


MOUNTING COMPATIBILITY

CODE VALVE	DESCRIPTION	COIL	POWER
ADC3...	Directional control valve	A09	27 W
AD3E...	Directional control valve	D15	30 W

OVERALL DIMENSION



ADC3...
VERSION



AD3E..
VERSION

Support plane specifications

