


C-RED


CONE-END REDUCER WITH SWIVEL (L/S, L, S, S/L)

24° Swivel (DIN EN ISO 8434-1) /
24° Tube Connection (DIN EN ISO 8434-1)



C-KOR





Series	PN [bar] C	PN [bar] CF	ØD1 [mm]	ØD2 [mm]	ØD3 [mm]	L1 [mm]	L2 [mm]	L3 [mm]	S1 [mm]	S2 [mm]	S3 [mm]	Ordering Code*	kg/ 100
S	400	400	25	6	4	45.5	38.5	53	32	46	17	**C-RED 25/06 S OMD**	30.6
			25	8	5	45.5	38.5	53	32	46	19	**C-RED 25/08 S OMD**	30.8
			25	10	7	45.5	38.0	54	32	46	22	**C-RED 25/10 S OMD**	31.0
			25	12	8	45.5	38.0	54	32	46	24	**C-RED 25/12 S OMD**	31.2
			25	14	10	47.5	39.5	57	32	46	27	**C-RED 25/14 S OMD**	31.8
			25	16	12	47.5	39.0	57	32	46	30	**C-RED 25/16 S OMD**	31.9
S/L	315	400	25	18	15	45.5	38.0	54	32	46	32	**C-RED 25 S/18 L OMD**	31.4
S	400	400	25	20	16	49.5	39.0	61	32	46	36	**C-RED 25/20 S OMD**	34.2
S/L	160	250	25	22	18	47.5	40.0	56	32	46	36	**C-RED 25 S/22 L OMD**	32.0
S	400	400	30	6	4	51.0	44.0	59	41	50	17	**C-RED 30/06 S OMD**	39.4
			30	8	5	51.0	44.0	59	41	50	19	**C-RED 30/08 S OMD**	39.6
			30	10	7	51.0	43.5	60	41	50	22	**C-RED 30/10 S OMD**	39.7
			30	12	8	51.0	43.5	60	41	50	24	**C-RED 30/12 S OMD**	40.0
			30	14	10	53.0	45.0	63	41	50	27	**C-RED 30/14 S OMD**	40.5
			30	16	12	53.0	44.5	63	41	50	30	**C-RED 30/16 S OMD**	40.6
			30	20	16	55.0	44.5	66	41	50	36	**C-RED 30/20 S OMD**	41.9
S/L	160	250	30	22	19	53.0	45.5	61	41	50	36	**C-RED 30 S/22 L OMD**	40.3
S	400	400	30	25	20	57.0	45.0	69	41	50	46	**C-RED 30/25 S OMD**	45.8
S/L	160	250	30	28	23	53.0	45.5	62	41	50	41	**C-RED 30 S/28 L OMD**	40.6
S	315	400	38	6	4	54.5	47.5	62	50	60	17	**C-RED 38/06 S OMD**	57.4
			38	8	5	54.5	47.5	62	50	60	19	**C-RED 38/04 S OMD**	57.7
			38	10	7	54.5	47.0	63	50	60	22	**C-RED 38/10 S OMD**	57.9
			38	12	8	54.5	47.0	63	50	60	24	**C-RED 38/12 S OMD**	58.1
			38	14	10	56.5	48.5	66	50	60	27	**C-RED 38/14 S OMD**	58.7
			38	16	12	56.5	48.0	68	50	60	30	**C-RED 38/16 S OMD**	58.9
			38	20	16	58.5	48.0	70	50	60	36	**C-RED 38/20 S OMD**	60.3
			38	25	20	60.5	48.5	73	50	60	46	**C-RED 38/25 S OMD**	62.4
S/L	160	250	38	28	24	56.5	49.0	66	50	60	41	**C-RED 38 S/28 L OMD**	59.1
S	315	400	38	30	25	62.5	49.0	76	50	60	50	**C-RED 38/30 S OMD**	64.6
S/L	160	250	38	35	30	58.5	48.0	70	50	60	50	**C-RED 38 S/35 L OMD**	60.7

*Replace the character "**C**" with "**CF**" when you require steel!
C = Stainless Steel, 1.4571 (Seal FKM) **CF** = Galvanized Steel Cr(VI)-free (Seal NBR)

CONEXA www.CONEXA.de Phone: +49 5541 9877 -0 Fax: +49 5541 9877 -77




C-KOR


CONE-END REDUCER WITH SWIVEL (L)

24° Shaft connector - Preassembled Shaft /
24° Tube Connection (DIN EN ISO 8434-1)









Series	PN [bar] C	PN [bar] CF	ØD1 [mm]	ØD2 [mm]	ØD3 [mm]	L1 [mm]	L2 [mm]	L3 [mm]	S1 [mm]	S2 [mm]	S3 [mm]	Ordering Code*	kg/ 100
L	315	315	8	6	4	33.5	26.5	41	12	17	14	**C-KOR 08/06 L OMD**	3.1
			10	6	4	34.5	27.5	42	12	19	14	**C-KOR 10/06 L OMD**	3.6
			10	8	6	35.5	28.5	43	14	19	17	**C-KOR 10/08 L OMD**	4.0
			12	6	4	36.5	29.5	44	14	22	14	**C-KOR 12/06 L OMD**	4.9
			12	8	6	36.5	29.5	44	14	22	17	**C-KOR 12/08 L OMD**	4.9
			12	10	8	37.5	30.5	45	17	22	19	**C-KOR 12/10 L OMD**	5.5
			15	6	4	37.0	30.0	45	17	27	14	**C-KOR 15/06 L OMD**	7.6
			15	8	6	37.0	30.0	45	17	27	17	**C-KOR 15/08 L OMD**	7.6
			15	10	8	38.0	31.0	46	17	27	19	**C-KOR 15/10 L OMD**	7.7
			15	12	10	39.0	32.0	47	19	27	22	**C-KOR 15/12 L OMD**	8.4
			18	6	4	37.5	30.5	45	19	32	14	**C-KOR 18/06 L OMD**	10.7
			18	8	6	37.5	30.5	45	19	32	17	**C-KOR 18/08 L OMD**	10.7
			18	10	8	38.5	31.5	46	19	32	19	**C-KOR 18/10 L OMD**	10.8
			18	12	10	38.5	31.5	46	19	32	22	**C-KOR 18/12 L OMD**	10.8
			18	15	12	39.5	32.5	48	24	32	27	**C-KOR 18/15 L OMD**	12.8
	160	160	22	6	4	38.5	31.5	46	24	36	14	**C-KOR 22/06 L OMD**	14.5
			22	8	6	38.5	31.5	46	24	36	17	**C-KOR 22/08 L OMD**	14.6
			22	10	8	39.5	32.5	47	24	36	19	**C-KOR 22/10 L OMD**	14.7
			22	12	10	39.5	32.5	47	24	36	22	**C-KOR 22/12 L OMD**	14.7
			22	15	12	40.5	33.5	49	24	36	27	**C-KOR 22/15 L OMD**	15.3
			22	18	15	41.5	34.0	50	27	36	32	**C-KOR 22/18 L OMD**	17.4

*Replace the character "**C**" with "**CF**" when you require steel!
C = Stainless Steel, 1.4571 **CF** = Galvanized Steel Cr(VI)-free

CONEXA www.CONEXA.de Phone: +49 5541 9877 -0 Fax: +49 5541 9877 -77





C-KOR

CONE-END REDUCER WITH SWIVEL (L)

24° Shaft connector - Preassembled Shaft /
24° Tube Connection (DIN EN ISO 8434-1)







Series	PN [bar] C	PN [bar] CF	ØD1 [mm]	ØD2 [mm]	ØD3 [mm]	L1 [mm]	L2 [mm]	L3 [mm]	S1 [mm]	S2 [mm]	S3 [mm]	Ordering Code*	kg/ 100
L	160	160	28	6	4	41.0	34.0	49	30	41	14	**C-KOR 28/06 L OMD**	18.9
			28	8	6	41.0	34.0	49	30	41	17	**C-KOR 28/08 L OMD**	18.9
			28	10	8	42.0	35.0	50	30	41	19	**C-KOR 28/10 L OMD**	19.1
			28	12	10	42.0	35.0	50	30	41	22	**C-KOR 28/12 L OMD**	19.1
			28	15	12	43.0	36.0	51	30	41	27	**C-KOR 28/15 L OMD**	19.7
			28	18	15	43.0	35.5	52	30	41	32	**C-KOR 28/18 L OMD**	20.0
			28	22	19	45.0	37.5	54	32	41	36	**C-KOR 28/22 L OMD**	20.7
			35	6	4	48.5	41.5	56	36	50	14	**C-KOR 35/06 L OMD**	30.1
			35	8	6	48.5	41.5	56	36	50	17	**C-KOR 35/08 L OMD**	30.1
			35	10	8	49.5	42.5	57	36	50	19	**C-KOR 35/10 L OMD**	30.3
			35	12	10	49.5	42.5	57	36	50	22	**C-KOR 35/12 L OMD**	30.3
			35	15	12	50.5	43.5	59	36	50	27	**C-KOR 35/15 L OMD**	30.9
			35	18	15	50.5	43.0	59	36	50	32	**C-KOR 35/18 L OMD**	31.3
			35	22	19	52.5	45.0	61	36	50	36	**C-KOR 35/22 L OMD**	31.5
			35	28	24	52.5	45.0	62	41	50	41	**C-KOR 35/28 L OMD**	33.5
			42	10	8	52.5	45.5	60	46	60	19	**C-KOR 42/10 L OMD**	47.4
			42	12	10	52.5	45.5	60	46	60	22	**C-KOR 42/12 L OMD**	47.5
			42	15	12	53.5	46.5	62	46	60	27	**C-KOR 42/15 L OMD**	48.1
			42	18	15	53.5	46.0	62	46	60	32	**C-KOR 42/18 L OMD**	48.5
			42	22	19	55.5	48.0	64	46	60	36	**C-KOR 42/22 L OMD**	48.8
			42	28	24	55.5	48.0	65	46	60	41	**C-KOR 42/28 L OMD**	48.8
			42	35	30	57.5	47.0	69	46	60	50	**C-KOR 42/35 L OMD**	50.1

*Replace the character "**C**" with "**CF**" when you require steel!
C = Stainless Steel, 1.4571 **CF** = Galvanized Steel Cr(VI)-free

CONEXA www.CONEXA.de Phone: +49 5541 9877 -0 Fax: +49 5541 9877 -77




C-KOR


CONE-END REDUCER WITH SWIVEL (S)

24° Shaft connector - Preassembled Shaft /
24° Tube Connection (DIN EN ISO 8434-1)









Series	PN [bar] C	PN [bar] CF	ØD1 [mm]	ØD2 [mm]	ØD3 [mm]	L1 [mm]	L2 [mm]	L3 [mm]	S1 [mm]	S2 [mm]	S3 [mm]	Ordering Code*	kg/ 100
S	630	630	8	6	4	36.5	29.5	44	14	19	17	**C-KOR 08/06 S OMD**	4.4
			10	6	4	38.5	31.5	46	14	22	17	**C-KOR 10/06 S OMD**	6.1
			10	8	5	38.5	31.5	46	17	22	19	**C-KOR 10/08 S OMD**	6.5
			12	6	4	38.5	31.5	46	14	24	17	**C-KOR 12/06 S OMD**	6.7
			12	8	5	38.5	31.5	46	17	24	19	**C-KOR 12/08 S OMD**	7.3
			12	10	7	39.5	32.0	48	19	24	22	**C-KOR 12/10 S OMD**	7.8
			14	6	4	40.5	33.5	48	17	27	17	**C-KOR 14/06 S OMD**	9.5
			14	8	5	40.5	33.5	48	17	27	19	**C-KOR 14/08 S OMD**	9.7
			14	10	7	41.5	34.0	50	19	27	22	**C-KOR 14/10 S OMD**	10.2
			14	12	8	41.5	34.0	50	22	27	24	**C-KOR 14/12 S OMD**	11.2
	400	400	16	6	4	41.0	34.0	49	17	30	17	**C-KOR 16/06 S OMD**	11.2
			16	8	5	41.0	34.0	49	17	30	19	**C-KOR 16/08 S OMD**	11.4
			16	10	7	42.0	34.5	51	19	30	22	**C-KOR 16/10 S OMD**	12.0
			16	12	8	42.0	34.5	51	22	30	24	**C-KOR 16/12 S OMD**	12.7
			16	14	10	44.0	36.0	54	24	30	27	**C-KOR 16/14 S OMD**	13.8
			20	6	4	46.0	39.0	54	22	36	17	**C-KOR 20/06 S OMD**	17.3
			20	8	5	46.0	39.0	54	22	36	19	**C-KOR 20/08 S OMD**	17.5
			20	10	7	46.0	38.5	55	22	36	22	**C-KOR 20/10 S OMD**	17.6
			20	12	8	46.0	38.5	55	22	36	24	**C-KOR 20/12 S OMD**	17.8
			20	14	10	48.0	40.0	58	24	36	27	**C-KOR 20/14 S OMD**	18.7
			20	16	12	49.0	40.5	59	27	36	30	**C-KOR 20/16 S OMD**	19.8

*Replace the character "**C**" with "**CF**" when you require steel!
C = Stainless Steel, 1.4571 **CF** = Galvanized Steel Cr(VI)-free

CONEXA www.CONEXA.de Phone: +49 5541 9877 -0 Fax: +49 5541 9877 -77



C-KOR


CONE-END REDUCER WITH SWIVEL (S)


24° Shaft connector - Preassembled Shaft /
24° Tube Connection (DIN EN ISO 8434-1)



C-KOVO







Series	PN [bar] C	PN [bar] CF	ØD1 [mm]	ØD2 [mm]	ØD3 [mm]	L1 [mm]	L2 [mm]	L3 [mm]	S1 [mm]	S2 [mm]	S3 [mm]	Ordering Code*	kg/ 100
S	400	400	25	6	4	50.5	43.5	58	27	46	17	**C-KOR 25/06 S OMD**	32.5
			25	8	5	50.5	43.5	58	27	46	19	**C-KOR 25/08 S OMD**	32.7
			25	10	7	50.5	43.0	59	27	46	22	**C-KOR 25/10 S OMD**	32.8
			25	12	8	50.5	43.0	59	27	46	24	**C-KOR 25/12 S OMD**	33.0
			25	14	10	52.5	44.5	62	27	46	27	**C-KOR 25/14 S OMD**	33.5
			25	16	12	52.5	44.0	62	27	46	30	**C-KOR 25/16 S OMD**	33.5
			25	20	16	54.5	44.0	66	32	46	36	**C-KOR 25/20 S OMD**	37.3
			30	6	4	53.0	46.0	61	32	50	17	**C-KOR 30/06 S OMD**	37.2
			30	8	5	53.0	46.0	64	32	50	19	**C-KOR 30/08 S OMD**	37.4
			30	10	7	53.0	45.5	62	32	50	22	**C-KOR 30/10 S OMD**	37.5
			30	12	8	53.0	45.5	62	32	50	24	**C-KOR 30/12 S OMD**	37.8
			30	14	10	55.0	47.0	64	32	50	27	**C-KOR 30/14 S OMD**	38.3
			30	16	12	55.0	46.5	65	32	50	30	**C-KOR 30/16 S OMD**	38.4
			30	20	16	57.0	46.5	68	32	50	36	**C-KOR 30/20 S OMD**	39.6
			30	25	20	60.0	48.0	72	41	50	46	**C-KOR 30/25 S OMD**	48.0
	250	315	38	6	4	60.0	53.0	68	41	60	17	**C-KOR 38/06 S OMD**	58.4
			38	8	5	60.0	53.0	68	41	60	19	**C-KOR 38/08 S OMD**	58.6
			38	10	7	60.0	52.5	69	41	60	22	**C-KOR 38/10 S OMD**	58.8
			38	12	8	60.0	52.5	69	41	60	24	**C-KOR 38/12 S OMD**	59.0
			38	14	10	62.0	54.0	2	41	60	27	**C-KOR 38/14 S OMD**	59.5
			38	16	12	62.0	53.5	72	41	60	30	**C-KOR 38/16 S OMD**	59.6
			38	20	16	64.0	53.5	75	41	60	36	**C-KOR 38/20 S OMD**	60.9
			38	25	20	66.0	54.0	78	41	60	46	**C-KOR 38/25 S OMD**	62.8
			38	30	25	69.0	55.5	82	46	60	50	**C-KOR 38/30 S OMD**	68.2

*Replace the character "**C**" with "**CF**" when you require steel!
C = Stainless Steel, 1.4571 **CF** = Galvanized Steel Cr(VI)-free

CONEXA www.CONEXA.de Phone: +49 5541 9877 -0 Fax: +49 5541 9877 -77





C-KOVO

SWIVEL REDUCER

24° Swivel (DIN EN ISO 8434-1) /
24° Tube Connection (DIN EN ISO 8434-1)







Series	PN [bar] C	PN [bar] CF	ØD1 [mm]	ØD2 [mm]	ØD3 [mm]	L1 [mm]	L2 [mm]	L3 [mm]	S1 [mm]	S2 [mm]	S3 [mm]	Ordering Code*	kg/ 100
L	315	500	6	8	2.5	31.5	24.5	39.5	14	14	17	**C-KOVO 06/08 L OMD**	2.6
L/S	315	500	6	8	2.5	33.5	26.5	41.5	17	14	19	**C-KOVO 06 L/08 S OMD**	3.5
L	315	500	6	10	2.5	32.5	25.5	40.5	17	14	19	**C-KOVO 06/10 L OMD**	3.0
L/S	315	500	6	10	2.5	34.5	27.0	43.5	19	14	22	**C-KOVO 06 L/10 S OMD**	4.1
L	315	400	6	12	2.5	33.5	26.5	41.5	19	14	22	**C-KOVO 06/12 L OMD**	3.6
L/S	315	500	6	12	2.5	34.5	27.0	43.5	22	14	24	**C-KOVO 06 L/12 S OMD**	4.9
	315	500	6	14	2.5	36.5	28.5	46.5	24	14	27	**C-KOVO 06 L/14 S OMD**	5.8
L	315	400	6	15	2.5	34.5	27.5	42.5	24	14	27	**C-KOVO 06/15 L OMD**	5.2
	315	500	8	10	4.0	32.5	25.5	40.5	17	17	19	**C-KOVO 08/10 L OMD**	3.8
L/S	315	500	8	10	4.0	34.5	27.0	43.5	19	17	22	**C-KOVO 08 L/10 S OMD**	4.8
L	315	400	8	12	4.0	33.5	26.5	41.5	19	17	22	**C-KOVO 08/12 L OMD**	4.3
L/S	315	500	8	12	4.0	34.5	27.0	43.5	22	17	24	**C-KOVO 08 L/12 S OMD**	5.6
	315	500	8	14	4.0	36.5	28.5	46.5	24	17	27	**C-KOVO 08 L/14 S OMD**	6.6
L	315	400	8	15	4.0	34.5	27.5	42.5	24	17	27	**C-KOVO 08/15 L OMD**	5.8
L/S	315	500	10	10	6.0	34.0	26.5	43.0	19	19	22	**C-KOVO 10 L/10 S OMD**	5.2
L	315	400	10	12	6.0	33.0	26.0	41.0	19	19	22	**C-KOVO 10/12 L OMD**	4.6
L/S	315	500	10	12	6.0	34.0	26.5	43.0	22	19	24	**C-KOVO 10 L/12 S OMD**	5.8
	315	500	10	14	6.0	36.0	28.0	46.0	24	19	27	**C-KOVO 10 L/14 S OMD**	6.7
L	315	400	10	15	6.0	34.0	27.0	42.0	24	19	27	**C-KOVO 10/15 L OMD**	6.0
L/S	315	500	10	16	6.0	37.0	28.5	47.0	27	19	30	**C-KOVO 10 L/16 S OMD**	7.9
L	315	400	10	18	6.0	35.0	27.5	44.0	27	19	32	**C-KOVO 10/18 L OMD**	7.5
L/S	315	400	12	12	8.0	34.0	26.5	43.0	22	22	24	**C-KOVO 12 L/12 S OMD**	6.7
	315	400	12	14	8.0	36.0	28.0	46.0	24	22	27	**C-KOVO 12 L/14 S OMD**	7.6
L	315	400	12	15	8.0	34.0	27.0	42.0	24	22	27	**C-KOVO 12/15 L OMD**	6.9
L/S	315	400	12	16	8.0	37.0	28.5	47.0	27	22	30	**C-KOVO 12 L/16 S OMD**	8.8
L	315	400	12	18	8.0	35.0	27.5	44.0	27	22	32	**C-KOVO 12/18 L OMD**	8.3

*Replace the character "**C**" with "**CF**" when you require steel!
C = Stainless Steel, 1.4571 (Seal FKM) **CF** = Galvanized Steel Cr(VI)-free (Seal NBR)


CONEXA www.CONEXA.de Phone: +49 5541 9877 -0 Fax: +49 5541 9877 -77


C-KOVO

SWIVEL REDUCER

24° Swivel (DIN EN ISO 8434-1) /
24° Tube Connection (DIN EN ISO 8434-1)







Series	PN [bar] C	PN [bar] CF	ØD1 [mm]	ØD2 [mm]	ØD3 [mm]	L1 [mm]	L2 [mm]	L3 [mm]	S1 [mm]	S2 [mm]	S3 [mm]	Ordering Code*	kg/ 100
L/S	315	400	12	20	8.0	39.0	28.5	50.0	32	22	36	**C-KOVO 12 L/20 S OMD**	11.5
L	160	250	12	22	8.0	37.0	29.5	46.0	32	22	36	**C-KOVO 12/22 L OMD**	10.2
L/S	315	400	15	16	10.0	38.5	30.0	48.5	27	27	30	**C-KOVO 15 L/16 S OMD**	11.5
L	315	400	15	18	10.0	36.5	29.0	45.5	27	27	32	**C-KOVO 15/18 L OMD**	11.1
L/S	315	400	15	20	10.0	40.5	30.0	51.5	32	27	36	**C-KOVO 15 L/20 S OMD**	14.0
L	160	250	15	22	10.0	38.5	31.0	47.5	32	27	36	**C-KOVO 15/22 L OMD**	12.6
L/S	315	400	15	25	10.0	43.5	31.5	55.5	41	27	46	**C-KOVO 15 L/25 S OMD**	19.1
L	160	250	15	28	10.0	39.5	32.0	48.5	41	27	41	**C-KOVO 15/28 L OMD**	15.9
L/S	315	400	18	20	12.0	42.0	31.5	53.0	32	32	36	**C-KOVO 18 L/20 S OMD**	17.1
L	160	250	18	22	12.0	40.0	32.5	49.0	32	32	36	**C-KOVO 18/22 L OMD**	15.7
L/S	315	400	18	25	12.0	45.0	33.0	57.0	41	32	46	**C-KOVO 18 L/25 S OMD**	23.5
L	160	250	18	28	12.0	41.0	33.5	50.0	41	32	41	**C-KOVO 18/28 L OMD**	20.3
L/S	315	400	18	30	12.0	48.0	34.5	61.0	46	32	50	**C-KOVO 18 L/30 S OMD**	29.6
L	160	250	18	35	12.0	44.0	33.5	55.0	46	32	50	**C-KOVO 18/35 L OMD**	26.4
L/S	160	250	22	25	16.0	46.0	34.0	58.0	41	36	46	**C-KOVO 22 L/25 S OMD**	24.9
L	160	250	22	28	16.0	42.0	34.5	51.0	41	36	41	**C-KOVO 22/28 L OMD**	21.8
L/S	160	250	22	30	17.0	49.0	35.5	62.0	46	36	50	**C-KOVO 22 L/30 S OMD**	30.0
L	160	250	22	35	16.0	45.0	34.5	56.0	46	36	50	**C-KOVO 22/35 L OMD**	27.3
L/S	160	250	22	38	17.0	53.0	37.0	68.0	55	36	60	**C-KOVO 22 L/38 S OMD**	43.0
L	160	250	22	42	16.0	47.0	36.0	59.0	55	36	60	**C-KOVO 22/42 L OMD**	35.6
L/S	160	250	28	30	22.0	49.5	36.0	62.5	46	41	50	**C-KOVO 28 L/30 S OMD**	33.1
L	160	250	28	35	22.0	45.5	35.0	56.5	46	41	50	**C-KOVO 28/35 L OMD**	29.7
L/S	160	250	28	38	22.0	53.5	37.5	68.5	55	41	60	**C-KOVO 28 L/38 S OMD**	47.3
L	160	250	28	42	22.0	47.5	36.5	59.5	55	41	60	**C-KOVO 28/42 L OMD**	39.0
L/S	160	250	35	38	28.0	57.5	41.5	72.5	55	50	60	**C-KOVO 35 L/38 S OMD**	52.9
L	160	250	35	42	28.0	51.5	40.5	63.5	55	50	60	**C-KOVO 35/42 L OMD**	44.8

*Replace the character "**C**" with "**CF**" when you require steel!
C = Stainless Steel, 1.4571 (Seal FKM) **CF** = Galvanized Steel Cr(VI)-free (Seal NBR)

CONEXA
www.CONEXA.de Phone: +49 5541 9877 -0 Fax: +49 5541 9877 -77