

# Proportion Adapter


CHEN YING





CPS-1





CPB-1





PTT-1





CPT-1





CPV-1 Standard




CPV-1 with Nipple




ST-1




SS-1

## ◆Features

1. Proportion adapters work with resistance type lubricators and open-straight type distributors, such as A types, AE types, B types, CB types, AE grease nipple types, and BB grease nipple types.
2. The flow between lubrication points can be more accurate by applying proportion adapters of different flow rates.
3. The flow rate of the proportion adapter is proportional. For example, under the same usage conditions, the flow rate of CPS-3 is about twice that of CPS-2; the flow rate of ST-2 is about four times that of ST-0.
4. Please use a clean lubricant to avoid the accumulation of impurities inside the proportion adapter, which may affect the flow of discharge volume or block the lubricant from flowing through the adapters.

## ◆Technical Data and Dimensional Data

| Model | Inlet (Outer Thread) | Outlet (Outer Thread) | Suitable Lubricators | Suitable Viscosity | Flow Code | Flow Rate | | Internal Structure | Backflow Prevention | N.W. (g) |
|---|---|---|---|---|---|---|---|---|---|---|
| CPS | M8xP1.0 | PT1/8 | Resistance Type Grease Lubricators | Grease NLGI 000-0 | 1 | [1] | Less ↑ Discharge Volume ↓ More | Flow Restrictor | X | 10 |
| CPB | M8xP1.0 | M8xP1.0 | | | | | | | | 9 |
| PTT | PT1/8 | PT1/8 | Resistance Type Oil Lubricators | Oil 32-90 cSt@40°C | 2 | [2] | | | O | 10 |
| CPT | M8xP1.0 | PT1/8 | | | | | | | | 10 |
| CPV Standard | M8xP1.0 | M8xP1.0 | | | 3 | [4] | | | | 9 |
| CPV with Nipple | M8xP1.0 | M8xP1.0 | | | 4 | [8] | | | | 9 |
| | | | | | 5 | [16] | | | | |
| ST | M8xP1.0 | PT1/8 | Resistance Type Oil Lubricators | Oil 32-90 cSt@40°C | 0 | [2] | Less ↑ Discharge Volume ↓ More | Flow Hole | O | 9 |
| SS | M8xP1.0 | M8xP1.0 | | | 1 | [4] | | | | 8 |
| | | | | | 2 | [8] | | | | |
| | | | | | 3 | [16] | | | | |
| | | | | | 4 | [32] | | | | |
| | | | | | 5 | [64] | | | | |

## ◆Order Code (CPS, CPB, PTT, CPT, CPV)

CPS — 1 — ※

| Model | Outer Thread |
|---|---|
| CPS | M8xPT1/8 |
| CPB | M8xM8 |
| PTT | PT1/8xPT1/8 |
| CPT | M8xPT1/8 |
| CPV Standard | M8xM8 |
| CPV with Nipple | M8xM8 |

| Code | Flow Rate |
|---|---|
| 1 | [1] |
| 2 | [2] |
| 3 | [4] |
| 4 | [8] |
| 5 | [16] |

| Special Request | |
|---|---|
| S | Add Compression Sleeve and Nut |

## ◆Order Code (ST, SS)

ST — 1 — ※

| Model | Outer Thread |
|---|---|
| ST | M8xPT1/8 |
| SS | M8xM8 |

| Code | Flow Rate |
|---|---|
| 0 | [2] |
| 1 | [4] |
| 2 | [8] |
| 3 | [16] |
| 4 | [32] |
| 5 | [64] |

| Special Request | |
|---|---|
| S | Add Compression Sleeve and Nut |