General description

The gear pumps are designed for transforming the mechanical energy as energy of the working liquid (pressure and flow rate). They are simplified in construction and they have a relatively low cost. All these benefits ensure their wide application in the hydraulic systems.

Drive arangements

The pump drive may be direct or indirect (by gear, chains, or belt transmissions). Both drives should not impose axial or radial forces on the pump shaft. Oldham coupling serrated drive adapters are used with direct drive. For indirect drive refer to the manufacturer.

The gear pumps are designed to work at the conditions mentioned below:

- Working liquid: hydraulic oils with viscosity 16 ... 200 mm^2/s;
- Degree of filtration: 15 ... 25 ì m;
- Ambient temperature range: - 22 ... 55 °C;
- Fluid temperature range: - 25 ... 80 °C;
- Inlet pressure, absolute: 0.8 ... 2.2 bar;
- Fluid velocity (suctiun line) 0,5 ... 1 m/s
- Outlet pressure up to 250 bar.

The gear pumps made by "Caproni" are produced in 5 diferent groups: 00, 10, 20 and 20H, 30 and 40. The displacements of the pumps are in the range from 0.25 to 60 cm^3.

Group 00 q = 0.25 ... 2 cm^3;
Group 10 q = 1 ... 9.8 cm^3;
Group 20 q = 4.5 ... 25 cm^3;
Group 20H q = 15 ... 36 cm^3;
Group 30 q = 20 ... 60 cm^3;
Group 40 q = 46 ... 60 cm^3.

There are different variants of flanges, shafts and ports for each pump group (standard; Germany; USA ...).

We offer the next variants too:

- tandem pumps;
- pumps with build-in valves;
- reversible pumps;
- reversible gear motors.

Used symbols:

n - speed of rotation [min^{-1}];
p - pressure [bar];
q - displacement [cm^3];
η - total efficiency $\eta = \eta_q.\eta_{hm}$ [-];
η_{hm} - hydromechanical efficiency [-];
η_q - volumetric efficiency [-].


Commonly used formulas:

Flow: $Q = \frac{q.n.\eta}{1000}$ [l/min]

Torque: $M \cong \frac{q.p}{20.\pi}$ [N.m]

Drive power: $P = \frac{Q.p}{600}$ [kW]

A relationship between the direction of rotation and the place of the inlet and outlet ports of the pumps



How to order:

Group	Rotation	Displacement code	Drive shaft	Pump code	Ports
00 **10** **20** **30** **40**	**A** ↺ **C** ↻ **R** Ω		**X** - Through the front cover **Y** - Through the both covers	***(*)	- A flange with metric threads **P4**- A flange with UNC threads **M** - Metric **G** - GAS **U** - SAE J475

Group 00	
Code	cm^3
0,25	0,25
0,3	0,3
0,5	0,5
0,75	0,75
1	1
1,25	1,25
1,5	1,5
1,75	1,75
2	2

Group 10	
Code	cm^3
1	1
1,25	1,25
1,6	1,6
2	2
2,5	2,5
*2,65**	*2,65*
3,15	3,15
3,65	3,65
4,2	4,2
4,7*	*4,7*
5	5
5,7	5,7
6,1	6,1
7,4	7,4
8*	*8*
8,5	8,5
9,8	9,8

Group 20	
Code	cm^3
4,5	4,5
6,3	6,3
7*	7
8,2	8,2
10	10
11	11,3
12	12
14	14
15	15
16	16
17*	*17,3*
19	19
22	22
25	25
28	28
32	32
36	36


Group 20H	
Code	cm^3
15	15
16	16
19	19
22	22
25	25
28	28
32	32
36	36

Group 30	
Code	cm^3
20	20
22,5	22,5
25	25
28	28
32	32
36	36
42	42
46	46
50	50
55	55
60	60

Group 40	
Code	cm^3
36	36
42	42
46	46
50	50
55	55
60	60

Example: 20A14X073 - Hydraulic gear pump, 20 group, direction of rotation - counter clockwise, displacement 14 cm^3, modification 073.

* - These pumps - only under a special order



Type	Displacement	Flow		Pressure	max Speed	Dimension										
		at 1500 rpm	at max rpm	P_{nom}	n	A	B	Inlet					Outlet			
	cm^3/rev	l/min	l/min	bar	rpm	mm	mm	E	H	d		F	E	H	d	F
20A(C)15X464H	15	20,48	47,78	250	3500	55,6	106,8	52,7	26,2	3/8"-14UNC-2B		25	47,6	22	3/8"-14UNC-2B	18
20A(C)16X464H	16	22,08	51,52	250	3500	56,6	108,4									
20A(C)17,3X464H	17,3	23,87	55,71	230	3500	57,6	110,5									
20A(C)18,2X464H	18,2	25,39	59,24	210	3500	58,4	112,1									
20A(C)19X464H	19	26,51	61,85	200	3500	59	113,4									
20A(C)22X464H	22	31,02	72,38	180	3500	61,5	118,4									
20A(C)25X464H	25	35,63	83,13	160	3500	63,9	123,3									
20A(C)28X464H	28	40,32	67,20	130	2500	66,4	128,1									
20A(C)32X464H	32	46,08	76,80	120	2500	69,6	134,4									
20A(C)36X464H	36	51,84	86,40	100	2500	72,8	141									